


3-Position Recliner 1659-R

Overall Dimensions	28.5"w x 35"d x 42"h	Weight	102 lbs.
Seat Dimensions	21.5"w x 20"d x 20"h	Cubic Feet	38
Seat to Top of Back	27"	COM	6.25 yds.
Top of Arm to Floor	27"		
Extended Length	62"		
Exposed Wood	Beech		



Standard Features	Options Available
<ul style="list-style-type: none"> • Durable steel 3-position recliner mechanism • Upholstered arms, seat and back • Tight cushion • Tapered European Beech legs • Adjustable brown plastic screw-in glide 	<ul style="list-style-type: none"> • Wood arm caps • Poly arm caps • Thermofoil drop table • Hook • Push bar • Back bump guard • Casters, set of 4 (2 locking)

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • Frame rails 5/4 WHND kiln dried maple • Front filler rail 60 x 60 x 38 Baltic Birch
Back	<ul style="list-style-type: none"> • Top back post 8/4 WHND kiln dried maple • Rails use 5/4 construction • Bottom post 7/8 plywood • Front/back mount and support rail 5/4 WHND kiln dried maple
Upholstery	<ul style="list-style-type: none"> • 6.25 yds. required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples
Arms	<ul style="list-style-type: none"> • 8/4 kiln dried maple
Assembly	<ul style="list-style-type: none"> • Joints are assembled using dowels, glue, screws and corner blocks • The seat, back, arms and mechanism are assembled using 1/4" - 20 bolts and T-nuts No. 9 and No. 12 wood screws

Foam

Seat	<ul style="list-style-type: none"> • 6.5" premium grade fire retardant foam • 35 lb. compression • 1.8 density • Covered in 1.25 oz. of polyester fiber then cemented to the frame
Back	<ul style="list-style-type: none"> • 4.75" premium grade fire retardant foam • 27 lb. compression • 1.4 density • Covered in .75 oz. of polyester fiber then cemented to the frame • All foam is contour cut to fit the design