



**Sleep Chair 1659-S**

<b>Overall Dimensions</b>	32" w x 37.5" d x 33.5" h	<b>Weight</b>	150 lbs.
<b>Seat Dimensions</b>	25.5" w x 22" d x 18" h	<b>Cubic Feet</b>	29
<b>Seat to Top of Back</b>	20"	<b>COM</b>	8.25 yds.
<b>Top of Arm to Floor</b>	25"	<b>Exposed Wood</b>	
<b>Extended Length</b>	85.5"		
<b>Sleep Surface Length</b>	82		



**Sleep Loveseat w/ Casters 1659-2SC**

<b>Overall Dimensions</b>	32" w x 37.5" d x 33.5" h	<b>Weight</b>	150 lbs.
<b>Seat Dimensions</b>	25.5" w x 22" d x 18" h	<b>Cubic Feet</b>	29
<b>Seat to Top of Back</b>	20"	<b>COM</b>	8.25 yds.
<b>Top of Arm to Floor</b>	25"	<b>Exposed Wood</b>	
<b>Extended Length</b>	85.5"		
<b>Sleep Surface Length</b>	82		



Standard Features	Options Available
<ul style="list-style-type: none"> <li>Multi-Position Steel Frame Mechanism</li> <li>Upholstered Arms, Seat and Back</li> <li>Tight Cushions</li> <li>Two 2" Locking Casters on Back, Coalbox Caster in Front of 1659-2SC</li> <li>Non-Marring Adjustable Glides</li> </ul>	<ul style="list-style-type: none"> <li>Poly Arm Caps in Black</li> <li>Wood Arm Caps (specify finish)</li> <li>CAL TB 133 Certified</li> <li>Moisture Barrier</li> </ul>

**Standard Textile & Finish Selection**

<http://carolina.ofs.com/design/textiles>  
<http://carolina.ofs.com/design/finishes>

**Frame Construction**

- Seat/Back**
  - Frame constructed of 5/4 WHND kiln dried maple
- Arms**
  - Top/bottom rail and front back post 5/4 WHND kiln dried maple
  - Front post and top filler 8/4 WHND kiln dried maple
  - Front/back top post 5/4 WHND kiln dried maple
  - Top block is 5/4 WHND kiln dried maple
  - Bottom roll rail is 5/4 WHND kiln dried maple
- Assembly**
  - Joints are assembled using glue, dowels, screws and corner blocks
  - The seat, back, arms and mechanism are assembled using 1/4-20 bolts and t-nuts, No. 9 and No. 12 wood screws

**Foam**

- Seat**
  - 5" thick premium grade fire retardant foam
  - 45 lb. compression
  - 2.5 density
  - Covered in .75 oz of polyester fiber then cemented to the frame
- Sleep Surface**
  - 3.25" thick premium grade fire retardant foam
  - 45 lb. compression
  - 2.5 density
  - Covered in .75 oz of polyester fiber then cemented to the frame
  - All foam is contour cut to fit the design