

Lounge chair 5110-1
Single textiles

Overall Dimensions	42"w x 27.5"d x 18"h	COM 54"	2.25 yds.
Exposed Wood	European Beech	Cubic Feet	21
		Shipping Weight	75 lbs.
		Weight Rating	300 lbs.

Standard Features	Options Available
<ul style="list-style-type: none"> Fully upholstered European beech or satin aluminum tapered legs Wall-saver design Non-marring adjustable glides 	Legs <ul style="list-style-type: none"> Wood legs (European beech) Satin aluminum legs Powder-coated legs (standard, studio, or super matte)
	Power: <ul style="list-style-type: none"> Left and/or right-side facing power Located in the front of the waterfall seat (1) Power outlet or (1) USB-A + (1) USB-C Available in White, Black, and Storm Cord is 6' long

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> Side, seat, top, bottom and front rails ¾ hardwood plywood Seat panel ¾ hardwood plywood
Upholstery	<ul style="list-style-type: none"> Covers are upholstered to the frame using 1/2" stainless steel staples
Leg	<ul style="list-style-type: none"> 2" diameter x 3 7/8" tall cold roll steel tubing Welded 4x4 steel mounting plate Finished in satin nickel plating Black plastic end cap for glide surface
Assembly	<ul style="list-style-type: none"> Joints are assembled using glue, dowels, screws and corner blocks The seat, back and arms are assembled using 1/4" - 20 bolts and t-nuts, No. 9 and No. 12 wood screws

Foam

Seat	<ul style="list-style-type: none"> 4" premium grade foam CAL TB 117 Certified Fire Retardant 45 compression 2.5 lb. density Covered in 1.25 oz of polyester fiber then cemented to the frame
Back	<ul style="list-style-type: none"> 2" premium grade foam CAL 117 TB Certified Fire Retardant 30 compression 1.8 lb. density Covered in 1.25 oz. of polyester fiber then cemented to the frame All foam is contour cut to follow the design

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- | | |
|------------|--|
| Seat | <ul style="list-style-type: none"> • Side, seat, top, bottom and front rails ¾ hardwood plywood • Seat panel ¾ hardwood plywood |
| Upholstery | <ul style="list-style-type: none"> • Covers are upholstered to the frame using 1/2" stainless steel staples |
| Leg | <ul style="list-style-type: none"> • 2" diameter x 3 7/8" tall cold roll steel tubing • Welded 4x4 steel mounting plate • Finished in satin nickel plating • Black plastic end cap for glide surface |
| Assembly | <ul style="list-style-type: none"> • Joints are assembled using glue, dowels, screws and corner blocks • The seat, back and arms are assembled using 1/4" - 20 bolts and t-nuts, No. 9 and No. 12 wood screws |

Foam

- | | |
|------|--|
| Seat | <ul style="list-style-type: none"> • 4" premium grade foam • CAL TB 117 Certified Fire Retardant • 45 compression • 2.5 lb. density • Covered in 1.25 oz of polyester fiber then cemented to the frame |
| Back | <ul style="list-style-type: none"> • 2" premium grade foam • CAL 117 TB Certified Fire Retardant • 30 compression • 1.8 lb. density • Covered in 1.25 oz. of polyester fiber then cemented to the frame • All foam is contour cut to follow the design |