



**Lounge chair 5110-1**  
Single textiles

<b>Overall Dimensions</b>	26"w x 27.5"d x 32"h	<b>COM 54"</b>	3.75 yds.
<b>Seat Dimensions</b>	21"w x 20"d x 18"h	<b>Cubic Feet</b>	27
<b>Seat to Top of Back</b>	14"	<b>Shipping Weight - Armless</b>	60 lbs.
<b>Top of Arm to Floor</b>	25.25"	<b>Shipping Weight - With Arms</b>	70 lbs.
<b>Exposed Wood</b>	European Beech	<b>Weight Rating</b>	400 lbs.



**Lounge chair 5110-1-MT**  
Multiple textiles

<b>Overall Dimensions</b>	26"w x 27.5"d x 32"h	<b>COM 54"</b> - Seat	1.75 yds.
<b>Seat Dimensions</b>	21"w x 20"d x 18"h	<b>COM 54"</b> - Back	1.25 yds.
<b>Seat to Top of Back</b>	14"	<b>COM 54"</b> - Arm Panels	2 yds.
<b>Top of Arm to Floor</b>	25.25"	<b>Cubic Feet</b>	27
<b>Exposed Wood</b>	European Beech	<b>Shipping Weight - Armless</b>	60 lbs.
		<b>Shipping Weight - With Arms</b>	70 lbs.
		<b>Weight Rating</b>	400 lbs.




**Loveseat 5110-2**  
Single textiles

<b>Overall Dimensions</b>	47"w x 27.5"d x 32"h	<b>COM 54"</b>	5 yds.
<b>Seat Dimensions</b>	42"w x 20"d x 18"h	<b>Cubic Feet</b>	40
<b>Seat to Top of Back</b>	14"	<b>Shipping Weight - Armless</b>	90 lbs.
<b>Top of Arm to Floor</b>	25.25"	<b>Shipping Weight - With Arms</b>	100 lbs.
<b>Exposed Wood</b>	European Beech	<b>Weight Rating</b>	300 lbs. (per seat)



**Loveseat 5110-2-MT**  
Multiple textiles

<b>Overall Dimensions</b>	47"w x 27.5"d x 32"h	<b>COM 54"</b> - Seat	2.25 yds.
<b>Seat Dimensions</b>	42"w x 20"d x 18"h	<b>COM 54"</b> - Back	1.75 yds.
<b>Seat to Top of Back</b>	14"	<b>COM 54"</b> - Arm Panels	2 yds.
<b>Top of Arm to Floor</b>	25.25"	<b>Cubic Feet</b>	40
<b>Exposed Wood</b>	European Beech	<b>Shipping Weight - Armless</b>	90 lbs.
		<b>Shipping Weight - With Arms</b>	100 lbs.
		<b>Weight Rating</b>	300 lbs.



Standard Features	Options Available
<ul style="list-style-type: none"> <li>• Armless</li> <li>• Upholstered seat, back and sides</li> <li>• European beech or satin aluminum tapered legs</li> <li>• Wall-saver design</li> <li>• Non-marring adjustable glides</li> <li>• Clean-thru design</li> </ul>	<b>Arms</b> <ul style="list-style-type: none"> <li>• Arms are available in wood or metal</li> <li>• Metal arms are available in satin aluminum or any of powercoats</li> <li>• Poly arm caps (Black or Folkstone Grey)</li> <li>• Solid surface arm caps (Cameo White, Modern White, Medea, or Polaris)</li> </ul>
	<b>Legs</b> <ul style="list-style-type: none"> <li>• Wood legs (European beech)</li> <li>• Satin aluminum legs</li> <li>• Powder-coated legs (standard, studio, or super matte)</li> </ul>
	<b>Power:</b> <ul style="list-style-type: none"> <li>• Left and/or right-side facing power</li> <li>• Located in the front of the waterfall seat</li> <li>• (1) Power outlet or (1) USB-A + (1) USB-C</li> <li>• Available in White, Black, and Storm</li> <li>• Cord is 6' long</li> </ul>

## Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

## Frame Construction

Seat	<ul style="list-style-type: none"> <li>• Side, seat, top, bottom and front rails ¾ hardwood plywood</li> <li>• Seat panel ¾ hardwood plywood</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Upright, top tack front/back and center tack 4/4 maple</li> <li>• Corner block, back post and lower middle back ¾ hardwood plywood</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>• Covers are upholstered to the frame using 1/2" stainless steel staples</li> </ul>
Leg	<ul style="list-style-type: none"> <li>• 2" diameter x 3 7/8" tall cold roll steel tubing</li> <li>• Welded 4x4 steel mounting plate</li> <li>• Finished in satin nickel plating</li> <li>• Black plastic end cap for glide surface</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>• Joints are assembled using glue, dowels, screws and corner blocks</li> <li>• The seat, back and arms are assembled using 1/4" - 20 bolts and t-nuts, No. 9 and No. 12 wood screws</li> </ul>

## Foam

Seat	<ul style="list-style-type: none"> <li>• 4" premium grade foam</li> <li>• CAL TB 117 Certified Fire Retardant</li> <li>• 45 compression</li> <li>• 2.5 lb. density</li> <li>• Covered in 1.25 oz of polyester fiber then cemented to the frame</li> </ul>
Back	<ul style="list-style-type: none"> <li>• 2" premium grade foam</li> <li>• CAL 117 TB Certified Fire Retardant</li> <li>• 30 compression</li> <li>• 1.8 lb. density</li> <li>• Covered in 1.25 oz. of polyester fiber then cemented to the frame</li> <li>• All foam is contour cut to follow the design</li> </ul>