


Lounge Chair 5110-1 / 5110-1-MT

Overall Dimensions	26"w x 27.5"d x 32"h	COM 54"	4 yds.
Seat Dimensions	21"w x 20"d x 18"h	Weight	60 lbs.
Seat to Top of Back	14"	Cubic Feet	27
Exposed Wood	American ash		



Loveseat 5110-2 / 5110-2-MT

Overall Dimensions	47"w x 27.5"d x 32"h	COM 54"	5 yds.
Seat Dimensions	42"w x 20"d x 18"h	Weight	90 lbs.
Seat to Top of Back	14"	Cubic Feet	40
Exposed Wood	American ash		



Standard Features	Options Available
<ul style="list-style-type: none"> • Armless • Clean-thru design • Upholstered seat, back and sides • Wall-saver design • Tapered American ash legs • Non-marring adjustable glides 	<ul style="list-style-type: none"> • Left and/or right arms • Poly or solid surface arm caps • Wood, satin aluminum, or powder-coated legs • Left or right side facing power available in White, Black, and Storm

Straight Bench 5110-B42

Overall Dimensions	42"w x 27.5"d x 18"h	COM 54"	2.25 yds.
Seat Dimensions	n/a	Weight	75 lbs.
Seat to Top of Back	n/a	Cubic Feet	21
Exposed Wood	American ash		



Standard Features	Options Available
<ul style="list-style-type: none"> • Upholstered seat and sides • Wall-saver design • Tapered American ash legs • Non-marring adjustable glides 	<ul style="list-style-type: none"> • Wood, satin aluminum, or powder-coated legs • Left and/or right side facing power available in White, Black, and Storm

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • Side, seat, top, bottom and front rails ¾ hardwood plywood • Seat panel ¾ hardwood plywood
Back	<ul style="list-style-type: none"> • Upright, top tack front/back and center tack 4/4 maple • Corner block, back post and lower middle back ¾ hardwood plywood
Upholstery	<ul style="list-style-type: none"> • 3.75 yds. (chair), 5 yds. (loveseat) required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples
Leg	<ul style="list-style-type: none"> • 2" diameter x 3 7/8" tall cold roll steel tubing • Welded 4x4 steel mounting plate • Finished in satin nickel plating • Black plastic end cap for glide surface
Assembly	<ul style="list-style-type: none"> • Joints are assembled using glue, dowels, screws and corner blocks • The seat, back and arms are assembled using 1/4" - 20 bolts and t-nuts, No. 9 and No. 12 wood screws

Foam

Seat	<ul style="list-style-type: none"> • 4" premium grade foam • CAL TB 117 Certified Fire Retardant • 45 compression • 2.5 lb. density • Covered in 1.25 oz of polyester fiber then cemented to the frame
Back	<ul style="list-style-type: none"> • 2" premium grade foam • CAL 117 TB Certified Fire Retardant • 30 compression • 1.8 lb. density • Covered in 1.25 oz. of polyester fiber then cemented to the frame • All foam is contour cut to follow the design