



**3-Position High Leg Recliner 1707**

<b>Overall Dimensions</b>	26.5" w x 36" d x 43" h	<b>Weight</b>	102 lbs.	
<b>Seat Dimensions</b>	21.5" w x 21" d x 20" h	<b>Cubic Feet</b>	38	
<b>Seat to Top of Back</b>	28"	<b>COM</b>	5.75 yds.	
<b>Top of Arm to Floor</b>	24"			
<b>Extended Length</b>	65"			
<b>Exposed Wood</b>	Maple			

**3-Position Recliner with Casters 1707-C**

<b>Overall Dimensions</b>	26.5" w x 36" d x 43" h	<b>Weight</b>	96 lbs.	
<b>Seat Dimensions</b>	21.5" w x 21" d x 20" h	<b>Cubic Feet</b>	38	
<b>Seat to Top of Back</b>	28"	<b>COM</b>	5.75 yds.	
<b>Top of Arm to Floor</b>	24"			
<b>Extended Length</b>	65"			

Standard Features	Options Available
<ul style="list-style-type: none"> <li>• Durable steel 3-position recliner mechanism</li> <li>• Upholstered arms, seat and back</li> <li>• Tight cushion</li> <li>• Tapered Maple legs (1707)</li> <li>• 4" Swivel front casters with brake, 4" fixed rear</li> <li>• Adjustable chrome glide</li> </ul>	<ul style="list-style-type: none"> <li>• Wood arm caps</li> <li>• Poly arm caps</li> <li>• Thermofoil drop table</li> <li>• Hook</li> <li>• Push bar</li> <li>• Back bump guard</li> <li>• Casters, set of 4 (2 locking)</li> </ul>

**Standard Textile & Finish Selection**

<http://carolina.ofs.com/design-resources/textiles>  
<http://carolina.ofs.com/design-resources/finishes>

**Frame Construction**


<b>Seat</b>	<ul style="list-style-type: none"> <li>• Side and back rail 5/4 WHND kiln dried maple</li> <li>• Front rail 6/4 WHAD kiln dried maple</li> <li>• Front filler rail 60 x 60 x 38 Baltic Birch</li> </ul>
<b>Back</b>	<ul style="list-style-type: none"> <li>• Bottom post 7/8 plywood</li> <li>• Top back post 8/4 WHND kiln dried maple</li> <li>• Other back frame components 5/4 WHND kiln dried maple</li> </ul>
<b>Upholstery</b>	<ul style="list-style-type: none"> <li>• 5.75 yds. required based on 54" wide, plain goods</li> <li>• Covers are upholstered to the frame using 1/2" stainless steel staples</li> </ul>
<b>Arms</b>	<ul style="list-style-type: none"> <li>• Support block 5/4 WHND kiln dried maple</li> <li>• Back and front post, top and bottom rail 8/4 WHND kiln dried maple</li> </ul>
<b>Assembly</b>	<ul style="list-style-type: none"> <li>• Joints are assembled using dowels, glue, screws and corner blocks</li> <li>• The seat, back, arms and mechanism are assembled using 1/4" - 20 bolts and T-nuts No. 9 and No. 12 wood screws</li> </ul>

**Foam**

<b>Seat</b>	<ul style="list-style-type: none"> <li>• 6.5" premium grade fire retardant foam</li> <li>• 29 lb. compression</li> <li>• 1.8 density</li> <li>• Covered in 1.25 oz. of polyester fiber then cemented to the frame</li> </ul>
<b>Back</b>	<ul style="list-style-type: none"> <li>• 5" premium grade fire retardant foam</li> <li>• 22 lb. compression</li> <li>• 1.1 density</li> <li>• Covered in .75 oz. of polyester fiber then cemented to the frame</li> </ul>

**Wallsaver Recliner 1727**

<b>Overall Dimensions</b>	27" w x 36" d x 42.5" h	<b>Weight</b>	88 lbs.
<b>Seat Dimensions</b>	22" w x 21" d x 21" h	<b>Cubic Feet</b>	38
<b>Seat to Top of Back</b>	23"	<b>COM</b>	6.25 yds.
<b>Top of Arm to Floor</b>	26.5"		
<b>Extended Length</b>	65"		
<b>Exposed Wood</b>	N/A		



Standard Features	Options Available
<ul style="list-style-type: none"> <li>• direct drive activation synchronizes right and left sides for easy opening</li> <li>• 2.5" wall clearance</li> <li>• Upholstered arms, seat and back</li> <li>• Tight cushion</li> <li>• Adjustable chrome glide</li> </ul>	<ul style="list-style-type: none"> <li>• Wood arm caps</li> <li>• Poly arm caps</li> <li>• Thermofoil drop table</li> <li>• Hook</li> <li>• Push bar</li> <li>• Back bump guard</li> <li>• Casters, set of 4 (2 locking)</li> </ul>

**Standard Textile & Finish Selection**

<http://carolina.ofs.com/design-resources/textiles>  
<http://carolina.ofs.com/design-resources/finishes>

**Frame Construction**

Seat	<ul style="list-style-type: none"> <li>• Frame constructed of 5/4 WHND kiln dried maple</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Frame back post 1" EZ frame plywood</li> <li>• Other back components 5/4 WHND kiln dried maple</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>• 6.25 yds. required based on 54" wide, plain goods</li> <li>• Covers are upholstered to the frame using 1/2" stainless steel staples</li> </ul>
Arms	<ul style="list-style-type: none"> <li>• Assembly 5/4 and 8/4 kiln dried maple</li> <li>• Front and back gusset 4 x 8 x .5 EZ frame plywood</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>• Joints are assembled using dowels, glue, screws and corner blocks</li> <li>• The seat, back, arms and mechanism are assembled using 1/4" - 20 bolts and T-nuts No. 9 and No. 12 wood screws</li> </ul>

**Foam**

Seat	<ul style="list-style-type: none"> <li>• 3.75" premium grade fire retardant foam</li> <li>• 29 lb. compression</li> <li>• 1.8 density</li> <li>• Covered in 1.25 oz. of polyester fiber then cemented to the frame</li> </ul>
Back	<ul style="list-style-type: none"> <li>• 5" premium grade fire retardant foam</li> <li>• 22 lb. compression</li> <li>• 1.1 density</li> <li>• Covered in .75 oz. of polyester fiber then cemented to the frame</li> </ul>