

Sleep Chair 1759-S

Overall Dimensions	32" w x 35" d x 33.5" h	Weight	150 lbs.
Seat Dimensions	25.5" w x 22" d x 18" h	Cubic Feet	29
Seat to Top of Back	20"	COM	8.25 yds.
Top of Arm to Floor	25"	Exposed Wood	
Extended Length	85.5"		
Sleep Surface Length	82		



Standard Features	Options Available
<ul style="list-style-type: none"> • Multi-Position Steel Frame Mechanism • Upholstered Arms, Seat and Back • Tight Cushion • Non-Marring Adjustable Glides 	<ul style="list-style-type: none"> • Wood Arm Caps • Black Poly Arm Caps • Casters

Standard Textile & Finish Selection

<http://carolina.ofs.com/design/textiles>
<http://carolina.ofs.com/design/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • Frame constructed of 5/4 WHND kiln dried maple
Back	<ul style="list-style-type: none"> • Frame constructed of 5/4 WHND kiln dried maple
Arms	<ul style="list-style-type: none"> • Top/bottom rail and front back post 5/4 WHND kiln dried maple • Front post and top filler 8/4 WHND kiln dried maple • Front/back top post 5/4 WHND kiln dried maple • Top block 5/4 WHND kiln dried maple • Bottom roll rail 5/4 WHND kiln dried maple
Assembly	<ul style="list-style-type: none"> • Joints are assembled using glue, dowels, screws, and corner blocks • The seat, back, arms and mechanism are assembled using 1/4" - 20 bolts and T-nuts No. 9 and No. 12 wood screws

Foam

Seat	<ul style="list-style-type: none"> • 4 1/2" premium grade fire retardant foam • 35 lb. compression • 1.8 density • Covered in 1.25 oz. of polyester fiber then cemented to the frame
Back	<ul style="list-style-type: none"> • 2 1/2" premium grade fire retardant foam • 30 lb. compression • 1.8 density • Covered in .75 oz of polyester fiber then cemented to the frame • All foam is contour cut to fit the design