


Wallsaver Recliner 1727

Overall Dimensions	27" w x 36" d x 42.5" h	Weight	88 lbs.
Seat Dimensions	22" w x 21" d x 21" h	Cubic Feet	38
Seat to Top of Back	23"	COM	6.25 yds.
Top of Arm to Floor	26.5"		
Extended Length	65"		
Exposed Wood	N/A		



Standard Features	Options Available
<ul style="list-style-type: none"> • direct drive activation synchronizes right and left sides for easy opening • 2.5" wall clearance • Upholstered arms, seat and back • Tight cushion • Adjustable chrome glide 	<ul style="list-style-type: none"> • Wood arm caps • Poly arm caps • Thermofoil drop table • Hook • Push bar • Back bump guard • Casters, set of 4 (2 locking)

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • Frame constructed of 5/4 WHND kiln dried maple
Back	<ul style="list-style-type: none"> • Frame back post 1" EZ frame plywood • Other back components 5/4 WHND kiln dried maple
Upholstery	<ul style="list-style-type: none"> • 6.25 yds. required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples
Arms	<ul style="list-style-type: none"> • Assembly 5/4 and 8/4 kiln dried maple • Front and back gusset 4 x 8 x .5 EZ frame plywood
Assembly	<ul style="list-style-type: none"> • Joints are assembled using dowels, glue, screws and corner blocks • The seat, back, arms and mechanism are assembled using 1/4 - 20 bolts and T-nuts No. 9 and No. 12 wood screws

Foam

Seat	<ul style="list-style-type: none"> • 3.75" premium grade fire retardant foam • 29 lb. compression • 1.8 density • Covered in 1.25 oz. of polyester fiber then cemented to the frame
Back	<ul style="list-style-type: none"> • 5" premium grade fire retardant foam • 22 lb. compression • 1.1 density • Covered in .75 oz. of polyester fiber then cemented to the frame