




Chair 680-1

| | | | | |
|----------------------------|------------------------|-------------------|---------|---|
| Overall Dimensions | 30"w x 33"d x 30"h | COM 54" | 5 yds. |  |
| Seat Dimensions | 25"w x 21.5"d x 16.5"h | Weight | 77 lbs. | |
| Seat to Top of Back | 13" | Cubic Feet | 25 | |
| Exposed Metal | American ash | | | |

Loveseat 680-2

| | | | | |
|----------------------------|------------------------|-------------------|----------|---|
| Overall Dimensions | 53"w x 33"d x 30"h | COM 54" | 6.5 yds. |  |
| Seat Dimensions | 50"w x 21.5"d x 16.5"h | Weight | 109 lbs. | |
| Seat to Top of Back | 13" | Cubic Feet | 40 | |
| Exposed Metal | American ash | | | |

Sofa 680-3

| | | | | |
|----------------------------|------------------------|-------------------|----------|---|
| Overall Dimensions | 80"w x 33"d x 30"h | COM 54" | 8.5 yds. |  |
| Seat Dimensions | 75"w x 21.5"d x 16.5"h | Weight | 140 lbs. | |
| Seat to Top of Back | 13" | Cubic Feet | 61 | |
| Exposed Metal | American ash | | | |

| Standard Features | Optional Features |
|--|---|
| <ul style="list-style-type: none"> • Upholstered arms, seat and back • Clean-thru design • American ash tapered wood legs • Wall-saver design • Non-Marring adjustable glides | <ul style="list-style-type: none"> • Resin arm caps • Solid surface arm caps • Powdercoated ferrules |

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

| | |
|----------------------|---|
| Seat | <ul style="list-style-type: none"> • 5" thick tapered poly over a .75" hardwood plywood seat board • Covered with 2.75" wide stretch webbing |
| Seat Back | <ul style="list-style-type: none"> • Tapered and radius cut poly over a ¾" hardwood plywood back board |
| Arms, Back, and Base | <ul style="list-style-type: none"> • Combination of ¾" plywood and solid hardwood |
| Upholstery | <ul style="list-style-type: none"> • Covers are upholstered to the frame using ½" stainless steel staples |
| Assembly | <ul style="list-style-type: none"> • Arms, back, and base are all pre-assembled using glue dowels, staples, and wood screws. • Upholstered pieces are attached using a combination of ¼-20 and ⅝-18 bolts |

Foam

| | |
|------|---|
| Seat | <ul style="list-style-type: none"> • 30 compression with 2.3 lb. density covered in .750" polyester fiber |
| Arms | <ul style="list-style-type: none"> • Combination of both 40 and 50 compression with 2.3 lb. density covered in .750" polyester fiber |