

Evergreen sleepover

76" Sleepover 6081-76 / 6081-76MT

Overall Dimensions	85"w x 36"d x 41"h	COM 54"	11.5 yds.	
Seat Dimensions	76"w x 26"d x 19"h	Shipping Weight	230	G. of the state of
Top of Arm to Floor	22"	Cubic Feet	95	
Sleep Surface Length	76"			

80" **Sleepover** 6081-80 / 6081-80MT

Overall Dimensions	89"w x 36"d x 41"h	COM 54"	15.5 yds.	
Seat Dimensions	80"w x 26"d x 19"h	Shipping Weight	240	Д — — — — — — — — — — — — — — — — — — —
Top of Arm to Floor	22"	Cubic Feet	95	
Sleep Surface Length	80"			
				T T T

Standard Features	Options Available
Two available sizes: 76" sleep surface and 80" sleep surface One single textile application Intuitive, fold down back for sleep surface Molded foam with sinuous spring for comfort Powder coated aluminum legs Storage cubbies located inside of exterior back Sure-Chek® on sleep surface Standard bumper trim on back Non-marring adjustable glides	 Powder coated aluminum leg (available in 4 finishes) or central locking casters Wood, resin or solid surface arm caps Tablet available in veneer, HPL or solid surface Powder coated tablet bracket available in 4 finishes Power available left and/or right side facing (available in 4 powder coats)

Standard Textile & Finish Selection

http://carolina.ofs.com/design/textiles http://carolina.ofs.com/design/finishes

Frame Construction

uction	
Seat	 .75" Russian birch plywood frame panel with webbing stretched over interior cutouts in the panel Contour cut foam applied Seat is secured by wood screws to the assembled wood base frame
Back	 .5" diameter solid steel rod inner frame with flat springs all embedded with a molded polymer body Hinged to both arms using a .375" diameter steel hinge pin
Back and base	 Assembled out of 3/4" thick Russian birch plywood
Arms	• Made up of a wood inner skeletal structure embedded in a firm inner structural polymer and then covered with a softer outer over-mold polymer
Power	Dual power units are 'daisy chained' together with one single power cord extending from the unit
Storage	 Storage cubbies standard on the inside face of the assembled back frame Polymer molded storage component in Cool Grey

Foam

Seat	•	6.8"	thick	profile	cut	toam

- Center core is 2.3 lb. density
- 30 compression with both side panels of 2.8 lb. density
- 50 compression and all covered with .9 oz fiber

carolina.ofs.com imagine a place® 800.521.5381 2020 Spec sheet 1 of 1