



Chair 678-1

Overall Dimensions	33.5"w x 33.5"d x 45"h	COM 54"	7 yds.	
Seat Dimensions	21"w x 21"d x 19.5"h	Shipping Weight	80 lbs.	
Seat to Top of Back	25.5"	Cubic Feet	35	
Top of Arm to Floor	24"	Exposed Wood	European Beech	

Loveseat 678-2

Overall Dimensions	54.5"w x 33.5"d x 45"h	COM 54"	9 yds.	
Seat Dimensions	42"w x 21"d x 19.5"h	Shipping Weight	150 lbs.	
Seat to Top of Back	25.5"	Cubic Feet	50	
Top of Arm to Floor	24"	Exposed Wood	European Beech	

Standard Features	Options Available
<ul style="list-style-type: none"> • Clean-Thru Design • Upholstered Arms, Seat and Back • Spring Seat • European Beech Wood Legs • Non-Removable Seat Cushion • Tapered European Beech Legs • Tack-In Non-Marring Glide 	<ul style="list-style-type: none"> • Various Finish Selections • Multiple Textile Applications

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	• All components made of kiln dried WHAD maple and plywood
Exposed Wood Parts	• Exposed wood parts are made of kiln dried european beech
Seat Board	• Wood seat EZ frame
Assembly	• Joints on seat, back and arms are assembled using glue, dowels, and narrow crown staples

Foam

Seat/Back	• Bonded glue seat, 5" thick, 2.5 lb density, 25 compression, premium grade CAL 117 certified
-----------	---

Suspension

Seat/Back/Arms	<ul style="list-style-type: none"> • Embedded coil springs • SYSTEX III sheet webbing comprised of; 100% polyester with a Tensile Strength of 200 lbs. per inch • ECOS Clips • No sag high loop springs • 2" helicals • LEXUS webbing • The webbing does contain about 40% latex, but is encapsulated by polypropylene yarn • 100% polypropylene • Latex coating is paranol acrylic 763 • Applied with 5/16 stainless steel staples
----------------	---