



Chair 220-1

Overall Dimensions	27.5"w x 29"d x 33"h	COM 54"	2 yds.
Seat Dimensions	23"w x 19"d x 18"h	Shipping Weight	44 lbs.
Seat to Top of Back	23"	Cubic Feet	15
Top of Arm to Floor	25"	Exposed Metal	




Loveseat 220-2

Overall Dimensions	50.5"w x 29"d x 33"h	COM 54"	4 yds.
Seat Dimensions	46"w x 19"d x 18"h	Shipping Weight	88 lbs.
Seat to Top of Back	23"	Cubic Feet	28
Top of Arm to Floor	25"	Exposed Metal	



Sofa 220-3

Overall Dimensions	73.75"w x 29"d x 33"h	COM 54"	6 yds.
Seat Dimensions	69"w x 19"d x 18"h	Shipping Weight	132 lbs.
Seat to Top of Back	23"	Cubic Feet	41
Top of Arm to Floor	25"	Exposed Metal	



Standard Features	Optional Features
<ul style="list-style-type: none"> • Upholstered Seat and Back • Push-Thru Design • Tight Cushion • Wall-Saver Design • Detailed Seams/Chamfered Wood Elements • Non-Marring Adjustable Glides 	<ul style="list-style-type: none"> • Resin arm caps • Solid surface arm caps

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Assembly • Mortise and tenon construction out of European Beech surrounding a metal angle iron support frame

Foam

Seat/Back • 4.75" premium grade foam
 • 0.5 oz fiber applied to the face
 • CAL TB 117 Certified Fire Retardant

Arms • Upholstered arm panels are covered with .25" thick foam inside and outside of 2.5 lbs, ILD:50

Suspension System

Seat • .75" thick plywood seat board with elastic strip webbing covering the center cutout
 • The upholstered seats are attached to the metal angle iron interior support frame

Back • .75" molded plywood attached to the wood frame via wood screws in the bottom of the back wood rail and locked into the back top of wood frame using key-slot locking mechanism