



Chair 921-1

| | | | |
|----------------------------|-------------------------|-------------------|---------|
| Overall Dimensions | 30" w x 28" d x 33.5" h | COM 54" | 5 yds. |
| Seat Dimensions | 25" w x 20" d x 18.5" h | Weight | 75 lbs. |
| Seat to Top of Back | 15" | Cubic Feet | 27 |
| Top of Arm to Floor | 25.5" | | |




Loveseat 921-2

| | | | |
|----------------------------|-------------------------|-------------------|---------|
| Overall Dimensions | 53" w x 28" d x 33.5" h | COM 54" | 7 yds. |
| Seat Dimensions | 49" w x 20" d x 18.5" h | Weight | 90 lbs. |
| Seat to Top of Back | 15" | Cubic Feet | 44 |
| Top of Arm to Floor | 25.5" | | |



Sofa 921-3

| | | | |
|----------------------------|-------------------------|-------------------|----------|
| Overall Dimensions | 78" w x 28" d x 33.5" h | COM 54" | 9 yds. |
| Seat Dimensions | 74" w x 20" d x 18.5" h | Weight | 120 lbs. |
| Seat to Top of Back | 15" | Cubic Feet | 66 |
| Top of Arm to Floor | 25.5" | | |



| Standard Features | Optional Features |
|--|--|
| <ul style="list-style-type: none"> Clean-thru design Upholstered arms, seat and back Tight cushion Curved Upholstered Front Panel for Easy Egress Legs 1" x 2" 16 Gauge Powder Coated Rectangular Tubing Steel Frame Seat Structure Non-Marring Adjustable Glides | <ul style="list-style-type: none"> Black Poly Arm Caps Wood Arm Caps |

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

| | |
|----------|---|
| Seat | <ul style="list-style-type: none"> 3/4" plywood frame panel with contoured cut foam applied |
| Back | <ul style="list-style-type: none"> 3/4" plywood back frame with contoured cut foam applied |
| Arms | <ul style="list-style-type: none"> 3/4" plywood arm frame wrapped in a thin layer of foam and upholstered |
| Legs | <ul style="list-style-type: none"> 1 x 2 16 gauge tubing (.06" wall thickness) with adjustable glides |
| Assembly | <ul style="list-style-type: none"> Seat assembly is connected to a 3/4" x 3/4" tube frame via 1/4" - 20 connector bolts Back assembly is bolted to inside of the two arms Seat assembly is attached to the inside of both arms as well as the back assembly 1" thick contoured upholstered bottom front modesty panel |

Foam

| | |
|------|--|
| Seat | <ul style="list-style-type: none"> 5" premium grade foam CAL TB 117 Certified Fire Retardant Bonded glue seat |
| Back | <ul style="list-style-type: none"> Premium grade foam CAL TB 117 Certified Fire Retardant Bonded glue front and rear back |

Suspension System

| | |
|----------------|--|
| Seat/Back/Arms | <ul style="list-style-type: none"> ECOS clips No sags high loop springs Helicals SYSTEX III sheet webbing comprised of; 100% polyester with a tensile strength of 200 lbs. per inch 100% polypropylene Latex coating is paranol acrylic 763 Applied with 5/16 stainless steel staples |
| Back | <ul style="list-style-type: none"> Premium grade foam CAL TB 117 Certified Fire Retardant Bonded glue front and rear back |