



Chair 921-1

Overall Dimensions	30" w x 28" d x 33.5" h	COM 54"	5 yds.
Seat Dimensions	25" w x 20" d x 18.5" h	Shipping Weight	75 lbs.
Seat to Top of Back	15"	Cubic Feet	27
Top of Arm to Floor	25.5"	Exposed Metal	Powder Coat




Loveseat 921-2

Overall Dimensions	53" w x 28" d x 33.5" h	COM 54"	7 yds.
Seat Dimensions	49" w x 20" d x 18.5" h	Shipping Weight	90 lbs.
Seat to Top of Back	15"	Cubic Feet	44
Top of Arm to Floor	25.5"	Exposed Metal	Powder Coat



Sofa 921-3

Overall Dimensions	78" w x 28" d x 33.5" h	COM 54"	9 yds.
Seat Dimensions	74" w x 20" d x 18.5" h	Shipping Weight	120 lbs.
Seat to Top of Back	15"	Cubic Feet	66
Top of Arm to Floor	25.5"	Exposed Metal	Powder Coat



Standard Features	Optional Features
<ul style="list-style-type: none"> Clean-Thru Design Upholstered arms, seat and back Tight Cushion Curved Upholstered Front Panel for Easy Egress Legs 1" x 2" 16 Gauge Powder Coated Rectangular Tubing Steel Frame Seat Structure Non-Marring Adjustable Glides 	<ul style="list-style-type: none"> Black Poly Arm Caps Wood Arm Caps

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- Seat • 3/4" plywood frame panel with contoured cut foam applied
- Back • 3/4" plywood back frame with contoured cut foam applied
- Arms • 3/4" plywood arm frame wrapped in a thin layer of foam and upholstered
- Legs • 1 x 2 16 gauge tubing (.06" wall thickness) with adjustable glides
- Assembly • Seat assembly is connected to a 3/4" x 3/4" tube frame via 1/4" - 20 connector bolts
- Back assembly is bolted to inside of the two arms
- Seat assembly is attached to the inside of both arms as well as the back assembly
- 1" thick contoured upholstered bottom front modesty panel

Foam

- Seat • 5" premium grade foam
- CAL TB 117 Certified Fire Retardant
- Bonded glue seat
- Back • Premium grade foam
- CAL TB 117 Certified Fire Retardant
- Bonded glue front and rear back

Suspension System

- Seat/Back/Arms • ECOS clips
- No sags high loop springs
- Helicals
- SYSTEX III sheet webbing comprised of; 100% polyester with a tensile strength of 200 lbs. per inch
- 100% polypropylene
- Latex coating is paranol acrylic 763
- Applied with 5/16 stainless steel staples
- Back • Premium grade foam
- CAL TB 117 Certified Fire Retardant
- Bonded glue front and rear back