

Guest Chair, Open Arm 1600

| | | | |
|----------------------------|--------------------------|------------------------|--------------------------------|
| Overall Dimensions | 24"w x 26"d x 34.5"h | COM 54" | 1.5 yds. |
| Seat Dimensions | 20.75"w x 22.25"d x 19"h | Shipping Weight | 38 lbs. |
| Seat to Top of Back | 15" | Cubic Feet | 19 |
| Top of Arm to Floor | 26.75" | Exposed Wood | European Beech or American Ash |



Guest Chair, Panel Arm 1610

| | | | |
|----------------------------|--------------------------|------------------------|--------------------------------|
| Overall Dimensions | 24"w x 26"d x 34.5"h | COM 54" | 2.25 yds. |
| Seat Dimensions | 20.75"w x 22.25"d x 19"h | Shipping Weight | 42 lbs. |
| Seat to Top of Back | 15" | Cubic Feet | 19 |
| Top of Arm to Floor | 26.75" | Exposed Wood | European Beech or American Ash |



| Standard Features | Options Available |
|---|---|
| <ul style="list-style-type: none"> • European Beech or American Ash frame and arm cap • Spring seat construction • Clean-Thru design • Upholstered seat and back • Wall-Saver design • Non-marring adjustable glide • Field replaceable components • SCS Indoor Advantage Gold Certified • Limited lifetime warranty | <ul style="list-style-type: none"> • Poly arm caps • Solid surface arm caps • Removable covers • Moisture barrier • Multiple textile application • CAL TB 133 Certified |

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- Seat**
 - All parts are made of WHAD kiln dried maple
 - Plywood seat EZ frame
- Back**
 - All components are made of WHAD kiln dried maple
- Upholstery**
 - All fabric and leather pieces are cut with automated cutters that utilize precise patterns
- Arms**
 - All parts are made of kiln dried European Beech or American Ash
- Assembly**
 - Joints are assembled using dowels, Mortise-and-Tenon, corner blocks, glue and #8/#10 screws

Foam

- Seat**
 - 2.25" premium grade foam
 - CAL TB 117 Certified Fire Retardant
 - 45 lb. compression
 - 2.5 density
- Back**
 - 1.25" premium grade foam
 - CAL TB 117 Certified Fire Retardant
 - 55 lb. compression
 - 2.5 density

Suspension

- Back**
 - 2430 Propex
 - 100% Polypropylene
 - "D" arc springs and spring clips
 - Applied with 5/16 stainless steel staples