


Guest chair, open arm 1600 / 1600-MT

Overall Dimensions	24"w x 26"d x 34.5"h	COM 54"	1.5 yds.
Seat Dimensions	20.75"w x 22.25"d x 19"h	Weight	38 lbs.
Seat to Top of Back	15"	Cubic Feet	19
Top of Arm to Floor	26.75"	Exposed Wood	European Beech or American Ash




Base loveseat, open arm 1600-L / 1600-L-MT

Overall Dimensions	45.5"w x 26"d x 34.5"h	COM 54"	2.5 yds.
Seat Dimensions	43.75"w x 26"d x 19"h	Weight	72 lbs.
Seat to Top of Back	15"	Cubic Feet	33
Top of Arm to Floor	26.75"		




Guest chair, panel arm 1610 / 1610-MT

Overall Dimensions	24"w x 26"d x 34.5"h	COM 54"	2.25 yds.
Seat Dimensions	20.75"w x 22.25"d x 19"h	Weight	42 lbs.
Seat to Top of Back	15"	Cubic Feet	19
Top of Arm to Floor	26.75"	Exposed Wood	European Beech or American Ash



Base loveseat, panel arm 1610-L / 1610-L-MT

Overall Dimensions	45.5"w x 26"d x 34.5"h	COM 54"	2.5 yds.
Seat Dimensions	43.75"w x 26"d x 19"h	Weight	72 lbs.
Seat to Top of Back	15"	Cubic Feet	33
Top of Arm to Floor	26.75"		



Standard Features	Options Available
<ul style="list-style-type: none"> • European Beech or American Ash frame and arm cap • Spring seat construction • Clean-Thru design • Upholstered seat and back • Wall-Saver design • Non-marring adjustable glide • Field replaceable components • SCS Indoor Advantage Gold Certified • Limited lifetime warranty 	<ul style="list-style-type: none"> • Poly arm caps • Solid surface arm caps • Removable covers • Moisture barrier • Multiple textile application • CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- Seat
 - All parts are made of WHAD kiln dried maple
 - Plywood seat EZ frame
- Back
 - All components are made of WHAD kiln dried maple
- Upholstery
 - All fabric and leather pieces are cut with automated cutters that utilize precise patterns
- Arms
 - All parts are made of kiln dried European Beech or American Ash
- Assembly
 - Joints are assembled using dowels, Mortise-and-Tenon, corner blocks, glue and #8/#10 screws

Foam

- Seat
 - 2.25" premium grade foam
 - CAL TB 117 Certified Fire Retardant
 - 45 lb. compression
 - 2.5 density
- Back
 - 1.25" premium grade foam
 - CAL TB 117 Certified Fire Retardant
 - 55 lb. compression
 - 2.5 density

Suspension

- Back
 - 2430 Propex
 - 100% Polypropylene
 - "D" arc springs and spring clips
 - Applied with 5/16 stainless steel staples