


Patient Chair, Open Arm 1625

Motion patient Chair, Open Arm 1625-Motion


Overall Dimensions	24" w x 26" d x 45" h	COM 54"	2 yds.
Seat Dimensions	20.75" w x 22.25" d x 19" h	Shipping Weight	41 lbs.
Seat to Top of Back	24"	Cubic Feet	24
Top of Arm to Floor	26.75"	Exposed Wood	European Beech or American Ash



Open Arm, Easy Access Chair 1675

Open Arm Motion, Easy Access Chair 1675-Motion

Overall Dimensions	24" w x 28.5" d x 39" h	COM 54"	1.5 yds.
Seat Dimensions	20.25" w x 19" d x 23.5" h	Shipping Weight	45 lbs.
Seat to Top of Back	15"	Cubic Feet	24
Top of Arm to Floor	32"	Exposed Wood	European Beech or American Ash




Standard Features	Options Available
<ul style="list-style-type: none"> • 1625-Motion and 1675-Motion mechanism designed specifically with up to 8° of smooth travel • Upholstered seat and back • Spring seat construction • Clean-thru design • Wallsaver design • European beech or american ash frame • Wood arm cap • Non-marring adjustable glides • Field replaceable components 	<ul style="list-style-type: none"> • Poly arm caps (black, taupe or grey) • Solid surface arm caps (cameo white, modern white, concrete, deep mink) • Removable covers

Patient Chair, Panel Arm 1635

Motion patient Chair, Panel Arm 1635-Motion


Overall Dimensions	24" w x 26" d x 45" h	COM 54"	2.75 yds.
Seat Dimensions	20.75" w x 22.25" d x 19" h	Shipping Weight	41 lbs.
Seat to Top of Back	24"	Cubic Feet	24
Top of Arm to Floor	26.75"	Exposed Wood	European Beech or American Ash



Panel Arm Easy Access Chair 1685

Panel Arm Motion Easy Access Chair 1685-Motion


Overall Dimensions	24" w x 28.5" d x 39" h	COM 54"	2.25 yds.
Seat Dimensions	20.5" w x 19" d x 23.5" h	Shipping Weight	45 lbs.
Seat to Top of Back	15"	Cubic Feet	24
Top of Arm to Floor	32"	Exposed Wood	European Beech or American Ash



Standard Features	Options Available
<ul style="list-style-type: none"> • 1635-Motion and 1685-Motion Mechanism Designed Specifically with up to 8° of Smooth Travel • Upholstered Arms, Seat and Back • Spring Seat Construction • Clean-Thru Design • Wallsaver Design • European Beech or American Ash Frame • Wood Arm Cap • Non-Marring Adjustable Glides • Field Replaceable Components 	<ul style="list-style-type: none"> • Poly arm caps (black, taupe or grey) • Solid surface arm caps (cameo white, modern white, concrete, deep mink) • Removable covers

Glider 1616

Overall Dimensions	26.5"w x 27.25"d x 39.25"h	COM 54"	4.25 yds.
Seat Dimensions	21"w x 19.75"d x 19.5"h	Shipping Weight	77 lbs.
Seat to Top of Arm	6.75"	Cubic Feet	22
Top of Arm to Floor	26.5"	Exposed Wood	European Beech or American Ash



Standard Features	Options Available
<ul style="list-style-type: none"> • Glider Mechanism Allows for 2-3 Inches of Glide Motion Front and Back • Locking Knob for Transportation Located on Mechanism Under Glider • Upholstered Arm Panels with No Arm Caps comes Standard • European Beech or American Ash if Wood Arm Caps are Specified • Plastic Glide Comes Standard with Glider Mechanism • Clean-Thru Design 	<ul style="list-style-type: none"> • Poly arm caps (black, taupe or grey) • Solid surface arm caps (cameo white, modern white, concrete or deep mink) • Back bump guard

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • Plywood seat EZ frame • All parts are made of WHAD kiln dried maple • Seat wedge; kiln dried WHAD maple (1625-Motion & 1625-Motion only)
Back	<ul style="list-style-type: none"> • All components are made of WHAD kiln dried maple
Upholstery	<ul style="list-style-type: none"> • All fabric and leather pieces are cut with automated cutters that utilize precise patterns
Arms	<ul style="list-style-type: none"> • All parts are made of kiln dried European Beech or American Ash
Assembly	<ul style="list-style-type: none"> • Joints on seat, back and arms are assembled using dowels, mortise-and-tenons, corner blocks, glue and #8/#10 screws

Foam

Seat/Back	<ul style="list-style-type: none"> • Premium Grade Foam • CAL TB 117 Certified Fire Retardant
-----------	---

Suspension

Back	<ul style="list-style-type: none"> • 2430 Propex <ul style="list-style-type: none"> • 100% Polypropylene • "D" Arc Springs and Spring Clips • Applied with 5/16" Stainless Steel Staples
------	---

Seat Pan and Travel Mechanism

- 7 gauge thick welded steel
- Seat and Back Support Brackets is of 7 gauge thick "C" Channel Steel (1625-Motion & 1625-Motion only)
- Mechanism is design specific with up to 8° of smooth travel, and has been tested to more than 145,000 cycles with no loss of torque (1625-Motion & 1625-Motion only)