


Recliner 1307

Overall Dimensions	34" w x 39" d x 48" h	Weight	145 lbs.
Seat Dimensions	24" w x 20" d x 20.25" h	Cubic Feet	50
Seat to Top of Back	30"	COM	6 yds.
Top of Arm to Floor	28"		
Extended Length	72"		



Standard Features	Options Available
<ul style="list-style-type: none"> • Durable steel recliner mechanism • Footrest and back operate independently of one another • Back can be infinitely positioned to any sleep position angle • Upholstered arms, seat and back • Tight cushion • Warm grey (with Silver Ion antimicrobial) powder coated steel release lever • 5" Fixed casters in the front, 5" swivel rear casters with brake 	<ul style="list-style-type: none"> • Wood arm caps in European Beech or American Ash • Poly arm caps (black, grey or taupe) • Solid surface arm caps (bisque, glacier white or Nocturne black) • Thermofoil drop table • Hook • Back bump guard • Black or white central locking casters • Black or white individual locking casters • Transporter base • Removable seat cover

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction


Seat	<ul style="list-style-type: none"> • Components are made of WHAD maple and plywood • Wood seat EZ frame
Back	<ul style="list-style-type: none"> • Exposed wood parts are made of kiln dried European Beech
Upholstery	<ul style="list-style-type: none"> • 6 yds. required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples
Assembly	<ul style="list-style-type: none"> • Joints on seat, back, and arms are assembled using dowels, glue and narrow crown staples

Foam

Seat	<ul style="list-style-type: none"> • Premium grade foam • CAL TB 117 Certified Fire Retardant • Bonded glue seat, 5" thick
Back	<ul style="list-style-type: none"> • Premium grade foam • CAL TB 117 Certified Fire Retardant • Bonded glue front and rear back

Lite Recliner 1307-SR

Overall Dimensions	32" w x 39" d x 48" h	Weight	145 lbs.
Seat Dimensions	22" w x 20" d x 20.25" h	Cubic Feet	38
Seat to Top of Back	27.75"	COM	6 yds.
Top of Arm to Floor	28"		
Extended Length	72"		



Standard Features	Options Available
<ul style="list-style-type: none"> • Durable steel recliner mechanism • Footrest and back operate independently of one another • Back can be infinitely positioned to any sleep position angle • Upholstered arms, seat and back • Tight cushion • Warm grey (with Silver Ion antimicrobial) powder coated steel release lever • 5" Fixed casters in the front, 5" swivel rear casters with brake 	<ul style="list-style-type: none"> • Wood arm caps in European Beech or American Ash • Poly arm caps (black, grey or taupe) • Solid surface arm caps (bisque, glacier white or Nocturne black) • Fold down arm • Thermofoil drop table • Hook • Push bar • Padded push bar • Back bump guard • Caster options • Pull out foot tray • Removable seat cover • Moisture barrier • Multiple textile application • CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction


Seat	<ul style="list-style-type: none"> • All components are made of WHAD maple • Wood seat EZ frame • Sheet webbing
Back	<ul style="list-style-type: none"> • All components are made of WHAD maple and plywood • Sheet webbing
Upholstery	<ul style="list-style-type: none"> • 6 yds. required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples
Arms	<ul style="list-style-type: none"> • All components are made of WHAD maple and plywood
Assembly	<ul style="list-style-type: none"> • Joints on seat, back, and arms are assembled using dowels, glue and narrow crown staples

Foam

Seat/Back	<ul style="list-style-type: none"> • Premium Grade Foam • CAL TB 117 Certified Fire Retardant
-----------	---

Bariatric Recliner 1307-OB

Overall Dimensions	39"w x 39"d x 48"h	Weight	155 lbs.
Seat Dimensions	29"w x 20"d x 20.25"h	Cubic Feet	50
Seat to Top of Back	30"	COM	6.5 yds.
Top of Arm to Floor	28"		
Extended Length	72"		



Standard Features	Options Available
<ul style="list-style-type: none"> Rated for 750 lbs. Durable steel recliner mechanism Footrest and back operate independently of one another Back can be infinitely positioned to any sleep position angle Upholstered arms, seat and back Tight cushion Warm grey (with Silver Ion antimicrobial) powder coated steel release lever 5" Fixed casters in the front, 5" swivel rear casters with brake 	<ul style="list-style-type: none"> Wood arm caps in European Beech or American Ash Poly arm caps (black, grey or taupe) Solid surface arm caps (bisque, glacier white or Nocturne black) Thermofoil drop table Hook Back bump guard Black or white central locking casters Black or white individual locking casters Transporter base Removable seat cover

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction


Seat	<ul style="list-style-type: none"> Components are made of WHAD maple and plywood Wood seat EZ frame
Back	<ul style="list-style-type: none"> Exposed wood parts are made of kiln dried European Beech
Upholstery	<ul style="list-style-type: none"> 6 yds. required based on 54" wide, plain goods Covers are upholstered to the frame using 1/2" stainless steel staples
Assembly	<ul style="list-style-type: none"> Joints on seat, back, and arms are assembled using dowels, glue and narrow crown staples

Foam

Seat	<ul style="list-style-type: none"> Premium grade foam CAL TB 117 Certified Fire Retardant Bonded glue seat, 5" thick
Back	<ul style="list-style-type: none"> Premium grade foam CAL TB 117 Certified Fire Retardant Bonded glue front and rear back

Recliner with Trendelenburg 1317

Overall Dimensions	40.75" w x 39" d x 48" h	Weight	168 lbs.
Seat Dimensions	24" w x 20" d x 20.25" h	Cubic Feet	50
Seat to Top of Back	30"	COM	6 yds.
Top of Arm to Floor	28"		
Extended Length	72"		



Standard Features	Options Available
<ul style="list-style-type: none"> Painted heavy gauge stamped steel lay flat recliner mechanism with heavy steel Trendelenburg release Footrest and back operate independently of one another Back can be infinitely positioned to any sleep position angle Upholstered arms, seat and back Tight cushion Warm Grey (with Silver Ion antimicrobial) powder coated steel foot release lever 5" Fixed casters in the front, 5" swivel rear casters with brake 	<ul style="list-style-type: none"> Wood arm caps in european beech or american ash Poly arm caps in black, grey or taupe Solid surface arm caps (bisque, glacier white, Nocturne black) Thermofoil drop table Fold down arm Drainage bag hook Heated seat and back Push bar Padded push bar Back bump guard Black or white central locking casters Black or white individual locking casters Transporter base Removable seat cover

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> Components are made of WHAD maple and plywood Wood seat EZ frame
Back	<ul style="list-style-type: none"> Exposed wood parts are made of kiln dried European Beech
Upholstery	<ul style="list-style-type: none"> 6 yds. required based on 54" wide, plain goods Covers are upholstered to the frame using 1/2" stainless steel staples
Assembly	<ul style="list-style-type: none"> Joints on seat, back, and arms are assembled using dowels, glue and narrow crown staples

Foam

Seat	<ul style="list-style-type: none"> Premium grade foam CAL TB 117 Certified Fire Retardant Bonded glue seat, 5" thick
Back	<ul style="list-style-type: none"> Premium grade foam CAL TB 117 Certified Fire Retardant Bonded glue front and rear back

Recliner, Open Arm 3-Position 1677-OA

Overall Dimensions	26.5"w x 33.25"d x 44"h	Weight	87 lbs.
Seat Dimensions	21"w x 20"d x 19"h	Cubic Feet	36
Seat to Top of Back	25"	COM	4.25 yds.
Top of Arm to Floor	25.25"	Exposed Wood	European Beech or American Ash
Extended Length	68.5"		



Standard Features	Options Available
<ul style="list-style-type: none"> • Durable steel push back 3-position recliner mechanism • Upholstered seat and back • Tight cushion • Open arm frame with wood arm cap • Wallsaver design • Non-marring adjustable glides • SCS Indoor Advantage Gold Certified • Limited lifetime warranty • Warranty - recliner components: 5 years 	<ul style="list-style-type: none"> • Wood arm caps in European Beech or American Ash • Poly arm caps (black, grey or taupe) • Solid surface arm caps (bisque, glacier white or Nocturne black) • Hook • Back bump guard • Moisture barrier • Multiple textile application • CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction


Seat	<ul style="list-style-type: none"> • All components are made of WHAD kiln dried maple
Back	<ul style="list-style-type: none"> • Frame back post 7/8 plywood • Pull rail 8/4 WHND kiln dried maple • All other back frame components 5/4 WHND kiln dried maple
Upholstery	<ul style="list-style-type: none"> • 4.25 yds. required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples
Arms	<ul style="list-style-type: none"> • Front post 6/4 WHAD kiln dried maple • Bottom, center and top rail 5/4 WHAD • Bottom filler 60 x 60 x 38 Baltic Birch
Assembly	<ul style="list-style-type: none"> • Joints are assembled using dowels, glue and corner blocks • The seat, back, arms and mechanism are assembled using 1/4" - 20 bolts and T-nuts No. 9 and No. 12 wood screws

Foam

Seat	<ul style="list-style-type: none"> • 4.5" premium grade fire retardant foam • 30 lb. compression • 1.8 density • Covered in .75 oz. of polyester fiber then cemented to the frame
Back	<ul style="list-style-type: none"> • 2.5" premium grade fire retardant foam • 30 lb. compression • 1.8 density • Covered in .75 oz. of polyester fiber then cemented to the frame • All foam is contour cut to fit the design

Recliner, Closed Arm 3-Position 1677

Overall Dimensions	26.5"w x 33.25"d x 44"h	COM 54"	6 yds.
Seat Dimensions	21"w x 20"d x 19"h	Shipping Weight	87 lbs.
Seat to Top of Back	25"	Cubic Feet	36
Top of Arm to Floor	25.25"	Exposed Wood	European Beech or American Ash
Extended Length	68.5"		



Standard Features	Options Available
<ul style="list-style-type: none"> • Durable steel push back 3-position recliner mechanism • Upholstered seat and back • Tight cushion • Must specify European Beech or American Ash legs • Upholstered arm panel without arm cap • Wallsaver design • Non-marring adjustable glides • SCS Indoor Advantage Gold Certified • Limited lifetime warranty • Warranty - recliner components: 5 years 	<ul style="list-style-type: none"> • Wood arm caps in European Beech or American Ash • Poly arm caps (black, grey or taupe) • Solid surface arm caps (bisque, glacier white or Nocturne black) • Thermofoil drop table • Hook • Back bump guard • Moisture barrier • Multiple textile application • CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction


Seat	<ul style="list-style-type: none"> • Components are made of WHAD maple and plywood • Wood seat EZ frame
Back	<ul style="list-style-type: none"> • Exposed wood parts are made of kiln dried European Beech
Upholstery	<ul style="list-style-type: none"> • 6 yds. required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples
Assembly	<ul style="list-style-type: none"> • Joints on seat, back, and arms are assembled using dowels, glue and narrow crown staples

Foam

Seat	<ul style="list-style-type: none"> • Premium grade foam • CAL TB 117 Certified Fire Retardant • Bonded glue seat, 5" thick
Back	<ul style="list-style-type: none"> • Premium grade foam • CAL TB 117 Certified Fire Retardant • Bonded glue front and rear back

Recliner, Closed Arm 3-Position with Casters 1677C

Overall Dimensions	26.5"w x 33.25"d x 44"h	COM 54"	6 yds.
Seat Dimensions	21"w x 20"d x 19"h	Shipping Weight	87 lbs.
Seat to Top of Back	25"	Cubic Feet	36
Top of Arm to Floor	25.25"	Exposed Wood	European Beech or American Ash
Extended Length	68.5"		



Standard Features	Options Available
<ul style="list-style-type: none"> • Durable steel push back 3-position recliner mechanism • Upholstered seat and back • Tight cushion • Upholstered arm panel without arm cap • (2) 5" Individual locking back casters in black • SCS indoor advantage gold certified • Limited lifetime warranty • Warranty - recliner components: 5 years 	<ul style="list-style-type: none"> • Wood arm caps in European Beech or American Ash • Poly arm caps (black, grey or taupe) • Solid surface arm caps (bisque, glacier white or Nocturne black) • Thermofoil drop table • Hook • Push bar • Padded push bar • Back bump guard • Moisture barrier • Multiple textile application • CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • Components are made of WHAD maple and plywood • Wood seat EZ frame
Back	<ul style="list-style-type: none"> • Exposed wood parts are made of kiln dried European Beech
Upholstery	<ul style="list-style-type: none"> • 6 yds. required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples
Assembly	<ul style="list-style-type: none"> • Joints on seat, back, and arms are assembled using dowels, glue and narrow crown staples

Foam

Seat	<ul style="list-style-type: none"> • Premium grade foam • CAL TB 117 Certified Fire Retardant • Bonded glue seat, 5" thick
Back	<ul style="list-style-type: none"> • Premium grade foam • CAL TB 117 Certified Fire Retardant • Bonded glue front and rear back