


**Bariatric chair open arms 1600-OB**  
Single textiles

<b>Overall Dimensions</b>	33"w x 26"d x 34.5"h	<b>COM 54"</b>	2 yds.
<b>Seat Dimensions</b>	29.75"w x 22.25"d x 19"h	<b>Cubic Feet</b>	26
<b>Seat to Top of Back</b>	15"	<b>Weight</b>	55 lbs.
<b>Top of Arm to Floor</b>	26.75"		



**Bariatric chair open arms 1600-OB-MT**  
Multiple textiles


<b>Overall Dimensions</b>	33"w x 26"d x 34.5"h	<b>COM 54" - Seat</b>	1.25 yds.
<b>Seat Dimensions</b>	29.75"w x 22.25"d x 19"h	<b>COM 54" - Back</b>	1.25 yds.
<b>Seat to Top of Back</b>	15"	<b>Cubic Feet</b>	26
<b>Top of Arm to Floor</b>	26.75"	<b>Weight</b>	55 lbs.



Standard Features	Options Available
<ul style="list-style-type: none"> <li>• 500 lbs. weight rating</li> <li>• European beech hardwood frame</li> <li>• Spring seat construction</li> <li>• Wall-saver design</li> <li>• Wood arm cap</li> <li>• Clean-thru design</li> <li>• Upholstered seat and back</li> <li>• Non-marring adjustable glides</li> </ul>	<ul style="list-style-type: none"> <li>• Poly arm caps (black or taupe)</li> <li>• Solid surface arm caps (Cameo White, Modern White, Medea, and Polaris)</li> <li>• Removeable covers</li> <li>• Moisture barrier</li> <li>• CAL TB 133 Certified</li> </ul>


**Bariatric chair panel arms 1610-OB**  
Single textiles

<b>Overall Dimensions</b>	33"w x 26"d x 34.5"h	<b>COM 54"</b>	2.75 yds.
<b>Seat Dimensions</b>	29.75"w x 22.25"d x 19"h	<b>Cubic Feet</b>	26
<b>Seat to Top of Back</b>	15"	<b>Weight</b>	59 lbs.
<b>Top of Arm to Floor</b>	26.75"		



**Bariatric chair panel arms 1610-OB-MT**  
Multiple textiles

<b>Overall Dimensions</b>	33"w x 26"d x 34.5"h	<b>COM 54" - Seat</b>	1.25 yds.
<b>Seat Dimensions</b>	29.75"w x 22.25"d x 19"h	<b>COM 54" - Back</b>	1.25 yds.
<b>Seat to Top of Back</b>	15"	<b>Cubic Feet</b>	26
<b>Top of Arm to Floor</b>	26.75"	<b>Weight</b>	59 lbs.



Standard Features	Options Available
<ul style="list-style-type: none"> <li>• 500 lbs. weight rating</li> <li>• European beech hardwood frame</li> <li>• Spring seat construction</li> <li>• Wall-saver design</li> <li>• Wood arm cap</li> <li>• Clean-thru design</li> <li>• Upholstered seat and back</li> <li>• Non-marring adjustable glides</li> </ul>	<ul style="list-style-type: none"> <li>• Poly arm caps (black or taupe)</li> <li>• Solid surface arm caps (Cameo White, Modern White, Medea, and Polaris)</li> <li>• Removeable covers</li> <li>• Moisture barrier</li> <li>• CAL TB 133 Certified</li> </ul>

**Standard Textile & Finish Selection**

---

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

**Frame Construction**

---

- |            |   |
|------------|---|
| Seat       | <ul style="list-style-type: none"><li>• All parts are made of WHAD kiln dried maple</li><li>• Plywood seat EZ frame</li></ul>                 |
| Back       | <ul style="list-style-type: none"><li>• All components are made of WHAD kiln dried maple</li></ul>  |
| Arms       | <ul style="list-style-type: none"><li>• All parts are made of kiln dried European Beech or American Ash</li></ul>                             |
| Upholstery | <ul style="list-style-type: none"><li>• All fabric and leather pieces are cut with automated cutters that utilize precise patterns</li></ul>  |
| Assembly   | <ul style="list-style-type: none"><li>• Joints are assembled using dowels, Mortise-and-Tenon, corner blocks, glue and #8/#10 screws</li></ul> |

**Foam**

---

- |      |  |
|------|--|
| Seat | <ul style="list-style-type: none"><li>• 2.25" premium grade foam</li><li>• CAL TB 117 Certified Fire Retardant</li><li>• 45 lb compression</li><li>• 2.5 density</li></ul> |
| Back | <ul style="list-style-type: none"><li>• 1.25" premium grade foam</li><li>• CAL TB 117 Certified Fire Retardant</li><li>• 55 lb compression</li><li>• 2.5 density</li></ul> |

**Suspension**

---

- |      |  |
|------|--|
| Back | <ul style="list-style-type: none"><li>• 2430 Propex (applied to backs)<ul style="list-style-type: none"><li>• 100% Polypropylene</li><li>• "D" arc springs and spring clips</li><li>• Applied with 5/16" stainless steel staples</li></ul></li></ul> |
|------|--|