



Guest chair, open arm 1600 / 1600-MT

Overall Dimensions	24"w x 26"d x 34.5"h	COM 54"	1.5 yds.
Seat Dimensions	20.75"w x 22.25"d x 19"h	Weight	38 lbs.
Seat to Top of Back	15"	Cubic Feet	19
Top of Arm to Floor	26.75"	Exposed Wood	European beech




Base loveseat, open arm 1600-L / 1600-L-MT

Overall Dimensions	45.5"w x 26"d x 34.5"h	COM 54"	2.5 yds.
Seat Dimensions	43.75"w x 26"d x 19"h	Weight	72 lbs.
Seat to Top of Back	15"	Cubic Feet	33
Top of Arm to Floor	26.75"		




Guest chair, panel arm 1610 / 1610-MT

Overall Dimensions	24"w x 26"d x 34.5"h	COM 54"	2.25 yds.
Seat Dimensions	20.75"w x 22.25"d x 19"h	Weight	42 lbs.
Seat to Top of Back	15"	Cubic Feet	19
Top of Arm to Floor	26.75"	Exposed Wood	European beech



Base loveseat, panel arm 1610-L / 1610-L-MT

Overall Dimensions	45.5"w x 26"d x 34.5"h	COM 54"	2.5 yds.
Seat Dimensions	43.75"w x 26"d x 19"h	Weight	72 lbs.
Seat to Top of Back	15"	Cubic Feet	33
Top of Arm to Floor	26.75"		



Standard Features	Options Available
• European beech frame and arm cap • Spring seat construction • Clean-Thru design • Upholstered seat and back • Wall-Saver design • Non-marring adjustable glide • Field replaceable components • SCS Indoor Advantage Gold Certified • Limited lifetime warranty	• Poly arm caps • Solid surface arm caps • Removable covers • Moisture barrier • Multiple textile application • CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- | | |
|------------|---|
| Seat | <ul style="list-style-type: none"> • All parts are made of WHAD kiln dried maple • Plywood seat EZ frame |
| Back | <ul style="list-style-type: none"> • All components are made of WHAD kiln dried maple |
| Upholstery | <ul style="list-style-type: none"> • All fabric and leather pieces are cut with automated cutters that utilize precise patterns |
| Arms | <ul style="list-style-type: none"> • All parts are made of kiln dried European beech |
| Assembly | <ul style="list-style-type: none"> • Joints are assembled using dowels, Mortise-and-Tenon, corner blocks, glue and #8/#10 screws |

Foam

- | | |
|------|--|
| Seat | <ul style="list-style-type: none"> • 2.25" premium grade foam • CAL TB 117 Certified Fire Retardant • 45 lb. compression • 2.5 density |
| Back | <ul style="list-style-type: none"> • 1.25" premium grade foam • CAL TB 117 Certified Fire Retardant • 55 lb. compression • 2.5 density |

Suspension

- | | |
|------|--|
| Back | <ul style="list-style-type: none"> • 2430 Propex <ul style="list-style-type: none"> • 100% Polypropylene • "D" arc springs and spring clips • Applied with 5/16 stainless steel staples |
|------|--|