

Patient chair 1468

Single textiles

Overall Dimensions	25"w x 25"d x 45"h	COM 54"	1.75 yds.
Seat Dimensions	20.5"w x 20.25"d x 18.5"h	Cubic Feet	26 ft.
Seat to Top of Back	26.5"	Shipping Weight	43 lbs.
Top of Arm to Floor	26"		
Top of Arm to Seat	7.5"		



Patient chair 1468-MT

Multiple textiles

Overall Dimensions	25"w x 25"d x 45"h	COM 54" - Seat	1 yds.
Seat Dimensions	20.5"w x 20.25"d x 18.5"h	COM 54" - Back	1.25 yds.
Seat to Top of Back	26.5"	COM 54" - Headrest	.75 yds.
Top of Arm to Floor	26"	Cubic Feet	26 ft.
Top of Arm to Seat	7.5"	Shipping Weight	43 lbs.



Standard Features	Options Available
• Open arm metal frame • Upholstered seat and back • Molded plywood back and webbed plywood seat construction • Molded foam seat and back • Fully welded, powder-coated metal frame • Rounded arm caps are available in resin or solid surface • Protective under-seat shroud (standard in black) • White nylon non-marring glides • Wall-saver design • Clean-thru design • Field-replaceable components • Baratric chair is weight rated to 600 lbs.	Arm caps • Resin (Black, Shadow, and Folkstone Grey) • Solid surface (Cameo White, Modern White, Medea, and Polaris)
	Frame • Powder-coated (standard, studio, and super matte powder coats)
	Additional options • Moisture barrier (seat and/or back) • Removable covers (seat only)

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	.875" plywood covered by Sytex sheet webbing
Back	.750" molded plywood
Frame	- Chair/table legs: 1.125" diameter, 11 gauge steel, .125" wall - Chair mating tabs: .625" diameter solid steel - Chair stretcher rails: 1.00" diameter, 11 gauge steel, .125" wall - Chair arm top straps: 1.125" x .250" thick steel - Chair back attachment brackets: 3" x 1.75" x .25" thick steel - Glides: White 1/4-20 thread, 5/8" diameter base x 1" threaded stem with nylon patch
Arm Caps	- Solid surface: .472" thick - Resin: .5" thick
Upholstery	All fabric and leather pieces are cut with automated cutters that utilize precise patterns

Foam

Seat Cushion	3 lb compression 40 density molded foam
Back Cushion	3 lb compression 40 density molded foam
Outside back	1.8 lb compression 50 density molded foam