



**Bariatric Chair 1408-OB**

<b>Overall Dimensions</b>	34" w x 27.5" d x 34" h	<b>COM 54"</b>	2 yds.	
<b>Seat Dimensions</b>	30" w x 19" d x 18" h	<b>Shipping Weight</b>	50 lbs.	
<b>Seat to Top of Back</b>	16.5"	<b>Cubic Feet</b>	26	
<b>Top of Arm to Floor</b>	25.5"	<b>Exposed Wood</b>	European Beech	

**Bariatric Chair 1408-K**

<b>Overall Dimensions</b>	35" w x 27.5" d x 34" h	<b>COM 54"</b>	2 yds.	
<b>Seat Dimensions</b>	30" w x 19" d x 18" h	<b>Shipping Weight</b>	67 lbs.	
<b>Seat to Top of Back</b>	16.5"	<b>Cubic Feet</b>	26	
<b>Top of Arm to Floor</b>	25.5"	<b>Exposed Wood</b>	European Beech	

Standard Features	Options Available
<ul style="list-style-type: none"> <li>• 500 lbs. weight rating (1408-OB)</li> <li>• 1000 lbs. weight rating (1408-K)</li> <li>• European Beech open arm frame with wood arm cap</li> <li>• European Beech exterior frame</li> <li>• Clean-Thru design</li> <li>• Upholstered seat and back</li> <li>• Non-marring adjustable glides</li> </ul>	<ul style="list-style-type: none"> <li>• Poly arm caps (black)</li> <li>• Removable covers</li> <li>• Moisture barrier</li> <li>• Multiple textile application</li> <li>• CAL TB 133 Certified</li> </ul>

**Standard Textile & Finish Selection**

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

**Frame Construction**

- |            |   |
|------------|---|
| Seat       | <ul style="list-style-type: none"> <li>• All parts are made of WHAD kiln dried maple</li> <li>• Plywood seat EZ frame</li> </ul>                |
| Back       | <ul style="list-style-type: none"> <li>• All components WHAD kiln dried maple</li> </ul>  |
| Arms       | <ul style="list-style-type: none"> <li>• Kiln dried European Beech</li> </ul>   |
| Upholstery | <ul style="list-style-type: none"> <li>• All fabric and leather pieces are cut with automated cutters that utilize precise patterns</li> </ul>  |
| Assembly   | <ul style="list-style-type: none"> <li>• Joints are assembled using dowels, Mortise-and-Tenon, corner blocks, glue and #8/#10 screws</li> </ul> |

**Foam**

- |      |  |
|------|--|
| Seat | <ul style="list-style-type: none"> <li>• 2.25" premium grade foam</li> <li>• CAL TB 117 Certified Fire Retardant</li> <li>• 45 lb. compression</li> <li>• 1.8 density</li> </ul> |
| Back | <ul style="list-style-type: none"> <li>• 1.5" premium grade foam</li> <li>• CAL TB 117 Certified Fire Retardant</li> <li>• 55 lb. compression</li> <li>• 2.5 density</li> </ul>  |

**Suspension**

- |      |   |
|------|---|
| Seat | <ul style="list-style-type: none"> <li>• LEXUS webbing <ul style="list-style-type: none"> <li>• Polypropylene/latex/rubber</li> </ul> </li> </ul>   |
| Back | <ul style="list-style-type: none"> <li>• 2430 Propex <ul style="list-style-type: none"> <li>• 100% Polypropylene</li> <li>• Latex coating is Paranol Acrylic 763</li> <li>• Applied with 5/16" stainless steel staples</li> </ul> </li> </ul> |