


Guest chair 1408 / 1408-MT

Overall Dimensions	25"w x 27.5"d x 34"h	COM 54"	1.5 yds.
Seat Dimensions	21"w x 19"d x 18"h	Weight	40 lbs.
Seat to Top of Back	16.5"	Cubic Feet	19
Top of Arm to Floor	25.5"	Exposed Wood	European Beech



Guest loveseat 1408-L / 1408-L-MT

Overall Dimensions	46.25"w x 27.5"d x 34"h	COM 54"	1.5 yds.
Seat Dimensions	41.25"w x 19"d x 18"h	Weight	70 lbs.
Seat to Top of Back	16.5"	Cubic Feet	36
Top of Arm to Floor	25.5"	Exposed Wood	European Beech



Standard Features	Options Available
<ul style="list-style-type: none"> Clean-thru design Upholstered seat and back European beech open arm frame with wood arm cap Wall-saver design Non-marring adjustable glides Field replaceable components 	<ul style="list-style-type: none"> Wood arm caps Poly arm caps (black) Removable covers

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> All parts are made of WHAD kiln dried maple Plywood seat EZ frame
Back	<ul style="list-style-type: none"> All components are made of WHAD kiln dried maple
Upholstery	<ul style="list-style-type: none"> All fabric and leather pieces are cut with automated cutters that utilize precise patterns
Arms	<ul style="list-style-type: none"> All parts are made of kiln dried European Beech
Assembly	<ul style="list-style-type: none"> Joints are assembled using dowels, Mortise-and-Tenon, corner blocks, glue and #8/#10 screws

Foam

Seat	<ul style="list-style-type: none"> 2.25" premium grade foam CAL TB 117 Certified Fire Retardant 45 lb. compression 1.8 density
Back	<ul style="list-style-type: none"> 1.5" premium grade foam CAL TB 117 Certified Fire Retardant 55 lb. compression 2.5 density

Suspension

Seat	<ul style="list-style-type: none"> LEXUS webbing <ul style="list-style-type: none"> Polypropylene/latex/rubber
Back	<ul style="list-style-type: none"> 2430 Propex <ul style="list-style-type: none"> 100% Polypropylene Latex coating is Paranol Acrylic 763 Applied with 5/16" stainless steel staples