



**Stationary patient chair 1825**

<b>Overall Dimensions</b>	22.75"w x 25.25"d x 44"h	<b>COM 54"</b>	2.25 yds.
<b>Seat Dimensions</b>	20.25"w x 20"d x 17.5"h	<b>Weight</b>	26 lbs.
<b>Seat to Top of Back</b>	26.5"	<b>Cubic Feet</b>	24
<b>Top of Arm to Floor</b>	25.5"	<b>Exposed Wood</b>	European Beech



**Motion back patient Chair 1825-MOTION**


<b>Overall Dimensions</b>	22.75"w x 25.25"d x 44"h	<b>COM 54"</b>	2.5 yds.
<b>Seat Dimensions</b>	20.25"w x 20"d x 17.5"h	<b>Weight</b>	26 lbs.
<b>Seat to Top of Back</b>	26.5"	<b>Cubic Feet</b>	24
<b>Top of Arm to Floor</b>	25.5"	<b>Exposed Wood</b>	European Beech



Standard Features	Options Available
<ul style="list-style-type: none"> <li>• European beech hardwood frame</li> <li>• Mortise-and-tenon construction</li> <li>• Clean-thru design</li> <li>• Field replaceable components</li> <li>• Wall-saver design</li> <li>• Non-marring adjustable glides</li> </ul>	<ul style="list-style-type: none"> <li>• Resin arm caps (black, taupe, and grey)</li> <li>• Solid surface arm caps</li> <li>• Black, taupe, or grey foot rest</li> <li>• Removable covers</li> </ul>


**Stationary easy access chair 1875**

<b>Overall Dimensions</b>	22.75"w x 27"d x 39.5"h	<b>COM 54"</b>	1.5 yds.
<b>Seat Dimensions</b>	20.25"w x 20"d x 24"h	<b>Weight</b>	28 lbs.
<b>Seat to Top of Back</b>	15"	<b>Cubic Feet</b>	24
<b>Top of Arm to Floor</b>	32"	<b>Exposed Wood</b>	European



**Motion seat easy access chair 1875-MOTION**

<b>Overall Dimensions</b>	22.75"w x 27"d x 39.5"h	<b>COM 54"</b>	1.75 yds.
<b>Seat Dimensions</b>	20.25"w x 20"d x 24"h	<b>Weight</b>	37 lbs.
<b>Seat to Top of Back</b>	15"	<b>Cubic Feet</b>	24
<b>Top of Arm to Floor</b>	32"	<b>Exposed Wood</b>	European



Standard Features	Options Available
<ul style="list-style-type: none"> <li>• European beech hardwood frame</li> <li>• Mortise-and-tenon construction</li> <li>• Clean-thru design</li> <li>• Field replaceable components</li> <li>• Wall-saver design</li> <li>• Non-marring adjustable glides</li> </ul>	<ul style="list-style-type: none"> <li>• Resin arm caps (black, taupe, and grey)</li> <li>• Solid surface arm caps</li> <li>• Black, taupe, or grey foot rest</li> <li>• Removable covers</li> </ul>

#### Standard Textile & Finish Selection

---

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

#### Frame Construction

---

- |          |   |
|----------|---|
| Seat     | <ul style="list-style-type: none"><li>• Hard plywood</li><li>• 1875-M support brackets is "C" Channel steel</li><li>• Mechanism for 1825-M is designed to have 8 degrees of smooth travel</li></ul> |
| Back     | <ul style="list-style-type: none"><li>• All components are made of curved plywood</li></ul>   |
| Arms     | <ul style="list-style-type: none"><li>• All components are made of solid European Beech</li></ul>   |
| Assembly | <ul style="list-style-type: none"><li>• Joints on seat, back, and arms are assembled using dowels, mortise-and-tenons, blocks, glue and #8/#10 screws</li></ul>                                     |

#### Foam

---

- |           |  |
|-----------|--|
| Seat/Back | <ul style="list-style-type: none"><li>• Premium Grade UC</li><li>• CAL TB 117 Certified Fire Retardant</li></ul> |
|-----------|--|

#### Suspension

---

- Seat and back is solid board construction