


**Patient Chair 1825**

<b>Overall Dimensions</b>	22.75" w x 25.25" d x 44" h	<b>COM 54"</b>	2 yds.
<b>Seat Dimensions</b>	20.25" w x 20" d x 17.5" h	<b>Shipping Weight</b>	26 lbs.
<b>Seat to Top of Back</b>	26.5"	<b>Cubic Feet</b>	24
<b>Top of Arm to Floor</b>	25.5"	<b>Exposed Wood</b>	European Beech Solids



Standard Features	Options Available
<ul style="list-style-type: none"> <li>• 500 lbs. Weight Rating</li> <li>• Solid Hardwood Frame</li> <li>• Mortise-and-Tenon Construction</li> <li>• Molded Foam Seat Construction</li> <li>• No Arm Cap</li> <li>• Clean-Thru Design</li> <li>• Field Replaceable Components</li> <li>• Wallsaver Design</li> <li>• Non-Marring Adjustable Glides</li> <li>• SCS Indoor Advantage Gold Certified</li> <li>• Limited Lifetime Warranty</li> </ul>	<ul style="list-style-type: none"> <li>• Resin Arm Caps in Black, Grey or Taupe</li> <li>• Removable Seat Cover</li> <li>• Moisture Barrier</li> <li>• Multiple Textile Application</li> <li>• CAL TB 133 Certified</li> </ul>

**Stationary Easy Access Chair 1875**

<b>Overall Dimensions</b>	22.75" w x 27" d x 39.5" h	<b>COM 54"</b>	1.5 yds.
<b>Seat Dimensions</b>	20.25" w x 20" d x 24" h	<b>Shipping Weight</b>	28 lbs.
<b>Seat to Top of Back</b>	15"	<b>Cubic Feet</b>	24
<b>Top of Arm to Floor</b>	25.5"	<b>Exposed Wood</b>	European Beech

**Motion Seat Easy Access Chair 1875-M**

<b>Overall Dimensions</b>	22.75" w x 27" d x 39.5" h	<b>COM 54"</b>	1.75 yds.
<b>Seat Dimensions</b>	20.25" w x 20" d x 24" h	<b>Shipping Weight</b>	37 lbs.
<b>Seat to Top of Back</b>	15"	<b>Cubic Feet</b>	24
<b>Top of Arm to Floor</b>	25.5"	<b>Exposed Wood</b>	European Beech

Standard Features	Options Available
<ul style="list-style-type: none"> <li>• Rated to 500 lbs.</li> <li>• European Beech Hardwood Frame</li> <li>• Mortise-and-Tenon Construction</li> <li>• Clean-Thru Design</li> <li>• Field Replaceable Components</li> <li>• Wall-Saver Design</li> <li>• Non-Marring Adjustable Glides</li> <li>• Greenguard Certified</li> <li>• Limited Lifetime Warranty</li> </ul>	<ul style="list-style-type: none"> <li>• Solid Surface Arm Caps</li> <li>• Resin Arm Caps</li> <li>• Polyurethane Coated Steel Foot Rest (black, taupe, or grey)</li> <li>• Moisture Barrier</li> <li>• CAL TB 133 Certified</li> <li>• Multiple Textile Application</li> </ul>

## Standard Textile & Finish Selection

---

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

## Frame Construction

---

- |          |   |
|----------|---|
| Seat     | <ul style="list-style-type: none"><li>• Hard plywood</li><li>• 1875-M support brackets is "C" Channel steel</li><li>• Mechanism for 1825-M is designed to have 8 degrees of smooth travel</li></ul> |
| Back     | <ul style="list-style-type: none"><li>• All components are made of curved plywood</li></ul>   |
| Arms     | <ul style="list-style-type: none"><li>• All components are made of solid European Beech</li></ul>   |
| Assembly | <ul style="list-style-type: none"><li>• Joints on seat, back, and arms are assembled using dowels, mortise-and-tenons, blocks, glue and #8/#10 screws</li></ul>                                     |

## Foam

---

- |           |  |
|-----------|--|
| Seat/Back | <ul style="list-style-type: none"><li>• Premium Grade UC</li><li>• CAL TB 117 Certified Fire Retardant</li></ul> |
|-----------|--|

## Suspension

---

- Seat and back is solid board construction