


Side Sleepover, Left Opening 7058-SSL

Side Sleepover, Right Opening 7058-SSR

Overall Dimensions	44" w x 34" d x 33.5" h	COM 54"	7.75 yds.
Seat Dimensions	40" w x 20" d x 20" h	Shipping Weight	187 lbs.
Seat to Top of Back	13"	Cubic Feet	40
Top of Arm to Floor	23.5"		
Sleep Surface Length	79.25"		



Standard Features	Options Available
<ul style="list-style-type: none"> Upholstered Arms, Seat, Back and Front Panel Semi-attached Folding Back Cushion Tight Seat Cushion Beige Antimicrobial Sleep Surface 1625" x 1.375" Brushed Aluminum Legs Metal Trundle Cart on Casters 2 Storage Cubbies inside Trundle Non-Marring Adjustable Glides EuroLuxe® Finishes with SilverBan® SCS Indoor Advantage Gold Certified Limited Lifetime Warranty 	<ul style="list-style-type: none"> Poly Arm Caps in Black Wood Arm Caps Non-Swivel Locking Casters - Set of 4 7"x15" Tablet in Wood Veneer with Satin Aluminum Swivel Connecting Arm (Left or Right Side Facing) Front Panel Options (Exposed Wood Front Panel or Laminate Front Panel) Moisture Barrier Multiple Textile Application CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/design/textiles>
<http://carolina.ofs.com/design/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> Seat consists of a thick piece of 5" thick foam setting on top of a seat box assembly Seat box assembly is made up of several 0.750" black melamine with pvc edge panels One side of the seat foam is hinged via Velcro to the seat box, which helps hold the seat in place when it is rotated over into the sleep position.
Back	<ul style="list-style-type: none"> Seat back is an assembled wood back made up of both plywood and solid wood of various thicknesses. Covered with a thin layer of propex and foam, then it is upholstered Seat back foam is two individual pieces of 4" thick foam hinges together so to lay flat when the unit is extended out
Upholstery	<ul style="list-style-type: none"> 11 yds. (7058-S76) 11.5 yds. (7058-S80) Required based on 54" wide, plain goods Covers are upholstered to the frame using 1/2" stainless steel staples
Arms	<ul style="list-style-type: none"> Both left and right arm assemblies are made up of various solid wood thicknesses For 7058-SSR, the right side facing arm extends out to the right creating a long sleep surface The left side facing arm is stationary and attached to both the seat box assembly and the assembled back For 7058-SSL, the left side facing arm would extend and the right side facing arm is stationary
Assembly	<ul style="list-style-type: none"> Whichever arm is designated as the extending arm, the metal rolling trundle cart is attached to the inside of that arm using (4) 5/16-18 bolts The metal trundle cart is made from .750 square tubing powdercoated black with (4) .750 thick black laminated insert panels When extended out from underneath the seat box assembly, the trundle cart has (2) large open cubbies for storage

Foam

Seat/Back	<ul style="list-style-type: none"> Premium Grade Foam CAL TB 117 Certified Fire Retardant
------------------	---