

## Bariatric Chair 1392-OB

<b>Overall Dimensions</b>	32.25"w x 25"d x 31.75"h	<b>COM 54"</b>	2 yds.
<b>Seat Dimensions</b>	30"w x 18.5"d x 18.5"h	<b>Weight</b>	38 lbs.
<b>Seat to Top of Back</b>	13.5"	<b>Cubic Feet</b>	33
<b>Top of Arm to Floor</b>	25.5"	<b>Exposed Metal</b>	Powder Coat

Standard Features	Options Available
<ul style="list-style-type: none"> <li>• 500 lbs. weight rating</li> <li>• ¾" tubular bent metal frame powder coated luster grey</li> <li>• Black resin arm cap</li> <li>• Clean-Thru design</li> <li>• Upholstered seat and back</li> <li>• Wall-Saver design</li> <li>• Tight cushion</li> <li>• Fitted non-marring glides</li> <li>• Field replaceable parts available</li> </ul>	<ul style="list-style-type: none"> <li>• Specify powder coat if different from luster grey</li> <li>• Wood arm caps</li> <li>• Removable covers</li> <li>• Moisture barrier</li> <li>• Multiple textile application</li> <li>• CAL TB 133 Certified</li> </ul>

## Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

## Frame Construction

Seat	<ul style="list-style-type: none"> <li>• ¾" Plywood seat frame panel</li> <li>• Seat springs spanning the openings in the plywood frame topped with contour cut foam</li> </ul>
Back	<ul style="list-style-type: none"> <li>• ¾" Plywood assembled back frame</li> <li>• Stretch webbing and foam applied to face</li> </ul>
Arms	<ul style="list-style-type: none"> <li>• ¾" (13 gauge) diameter bent powder coated metal tube</li> <li>• 1" thick black resin or Beech Wood arm cap attached along the top edge via machine screws from underneath</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>• All fabric and leather pieces are cut with automated cutters that utilize precise patterns</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>• Seat: Attached to a ¾" x ¾" (16 gauge) powder coated tube frame via ¼" - 20 connector bolts underneath the seat</li> <li>• Back: ¼" thick powder coated metal back brackets attached to the wood frame underneath the foam</li> <li>• Brackets and back assembly attached to the ¾" x ¾" powder coated tube frame via ¼" - 20 connector bolts under seat</li> </ul>

## Foam

Seat	<ul style="list-style-type: none"> <li>• 2.5" premium grade foam</li> <li>• CAL TB 117 Certified Fire Retardant</li> <li>• 45 lb. compression</li> <li>• 1.8 density</li> </ul>
Back	<ul style="list-style-type: none"> <li>• Premium grade foam</li> <li>• CAL TB 117 Certified Fire Retardant</li> </ul>

## Suspension

Seat	<ul style="list-style-type: none"> <li>• LEXUS webbing <ul style="list-style-type: none"> <li>• Polypropylene/latex/rubber</li> </ul> </li> </ul>
Back	<ul style="list-style-type: none"> <li>• 2430 Propex <ul style="list-style-type: none"> <li>• 100% Polypropylene</li> <li>• Latex coating is Paranol Acrylic 763</li> <li>• Applied with 5/16" stainless steel staples</li> </ul> </li> </ul>