

## Rule of Three bench

**48" Bench** 391-B48 Single textiles

Overall Dimensions $48"w \times 24"d \times 18.5"h$ COM 54"2.5 yds.Seat Dimensions $44"w \times 24"d \times 18.5"h$ Cubic Feet12Exposed MetalLuster GreyWeight45 lbs.

Weight Rating 275 lbs. (per seat)



**48" Bench** 391-B48-MT Multiple textiles

Overall Dimensions $48\text{"w} \times 24\text{"d} \times 18.5\text{"h}$ COM 54" - SeatSeat Dimensions $44\text{"w} \times 24\text{"d} \times 18.5\text{"h}$ COM 54" - Arm PanelsExposed MetalLuster GreyCubic Feet

Weight Rating 275 lbs. (per seat)

1.5 yds.

1.25 yds.



Standard Features	Options Available
Spring seat construction Tight cushion Fully upholstered Wall-saver design ¾" tubular bent Luster Grey powder-coated metal frame inset into upholstered end panel White plastic glide fitted into the bottom of tubular leg	Base     Powder-coated (standard or super matte powder coats)  Additional protection     Removable seat cover     Moisture barrier



## Rule of Three bench

## Standard Textile & Finish Selection

http://carolina.ofs.com/resources/textiles http://carolina.ofs.com/resources/finishes

## Frame Construction

Seat • 3/4" plywood seat frame panel with seat springs spanning the openings in plywood frame

• Topped with contour cut foam

Upholstery • Required based on 54" wide, plain goods

- Covers are upholstered to the frame using  $\frac{1}{2}$ " stainless steel staples

Seat • Attached to a  $\frac{3}{4}$ " x  $\frac{3}{4}$ " (16 ga.) powder coated tube frame via  $\frac{1}{4}$ " - 20 connector bolts

Foam

Seat • Premium grade foam

· CAL TB 117 Certified Fire Retardant