

Guest chair armless 1393

Single textiles

Overall Dimensions	23.5"w x 25"d x 31.75"h	COM 54"	1.5 yds.
Seat Dimensions	21.25"w x 18.5"d x 18.5"h	Cubic Feet	16
Seat to Top of Back	13.5"	Weight	35 lbs.
Exposed Metal	Luster Grey	Weight Rating	400 lbs.



Guest chair armless 1393-MT

Multiple textiles

Overall Dimensions	23.5"w x 25"d x 31.75"h	COM 54" - Seat	1 yds.
Seat Dimensions	21.25"w x 18.5"d x 18.5"h	COM 54" - Back	1 yds.
Seat to Top of Back	13.5"	Cubic Feet	16
Exposed Metal	Luster Grey	Weight	35 lbs.
		Weight Rating	400 lbs.



Guest loveseat armless 1393-L

Single textiles

Overall Dimensions	43.75"w x 25"d x 31.75"h	COM 54"	2.5 yds.
Seat Dimensions	41.5"w x 18.5"d x 18.5"h	Cubic Feet	36
Seat to Top of Back	13.5"	Weight	62 lbs.
Exposed Metal	Luster Grey	Weight Rating	275 lbs. (per seat)



Guest loveseat armless 1393-L-MT

Multiple textiles

Overall Dimensions	43.75"w x 25"d x 31.75"h	COM 54" - Seat	1.5 yds.
Seat Dimensions	41.5"w x 18.5"d x 18.5"h	COM 54" - Back	1.5 yds.
Seat to Top of Back	13.5"	Cubic Feet	36
Exposed Metal	Luster Grey	Weight	62 lbs.
		Weight Rating	275 lbs. (per seat)



Standard Features	Options Available
<ul style="list-style-type: none"> • Spring seat construction • Tight cushion • Upholstered seat and back • Clean-thru design • Wall-saver design • 3/4" tubular bent Luster Grey powder-coated metal frame • White plastic glide fitted into the bottom of tubular leg 	Base <ul style="list-style-type: none"> • Powder-coated (standard or super matte powder coats)
	Additional protection <ul style="list-style-type: none"> • Removable seat and/or back covers • Moisture barrier

Guest chair with arms 1392

Single textiles

Overall Dimensions	23.5"w x 25"d x 31.75"h	COM 54"	1.5 yds.
Seat Dimensions	21.25"w x 18.5"d x 18.5"h	Cubic Feet	16
Seat to Top of Back	13.5"	Weight	35 lbs.
Top of Arm to Floor	25.5"	Weight Rating	400 lbs.
Exposed Metal	Luster Grey		



Guest chair with arms 1392-MT

Multiple textiles

Overall Dimensions	23.5"w x 25"d x 31.75"h	COM 54" - Seat	1 yds.
Seat Dimensions	21.25"w x 18.5"d x 18.5"h	COM 54" - Back	1 yds.
Seat to Top of Back	13.5"	Cubic Feet	16
Top of Arm to Floor	25.5"	Weight	35 lbs.
Exposed Metal	Luster Grey	Weight Rating	400 lbs.



Guest loveseat with arms 1392-L

Single textiles

Overall Dimensions	43.75"w x 25"d x 31.75"h	COM 54"	2.5 yds.
Seat Dimensions	41.5"w x 18.5"d x 18.5"h	Cubic Feet	36
Seat to Top of Back	13.5"	Weight	62 lbs.
Top of Arm to Floor	25.5"	Weight Rating	275 lbs. (per seat)
Exposed Metal	Luster Grey		



Guest loveseat with arms 1392-L-MT

Multiple textiles

Overall Dimensions	43.75"w x 25"d x 31.75"h	COM 54" - Seat	1.5 yds.
Seat Dimensions	41.5"w x 18.5"d x 18.5"h	COM 54" - Back	1.5 yds.
Seat to Top of Back	13.5"	Cubic Feet	36
Top of Arm to Floor	25.5"	Weight	62 lbs.
Exposed Metal	Luster Grey	Weight Rating	275 lbs. (per seat)



Standard Features	Options Available
<ul style="list-style-type: none"> • Spring seat construction • Tight cushion • Upholstered seat and back • Clean-thru design • Wall-saver design • 3/4" tubular bent Luster Grey powder-coated metal frame • White plastic glide fitted into the bottom of tubular leg • Black resin arm cap is standard 	Arm caps <ul style="list-style-type: none"> • Resin (Black, Taupe, and Folkstone Grey)
	Base <ul style="list-style-type: none"> • Powder-coated (standard or super matte powder coats)
	Additional protection <ul style="list-style-type: none"> • Removable seat and/or back covers • Moisture barrier

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- | | |
|------------|--|
| Seat | <ul style="list-style-type: none"> • ¾" plywood seat frame panel • Seat springs spanning the openings in the plywood frame • Topped with contour cut foam |
| Back | <ul style="list-style-type: none"> • ¾" plywood assembled back frame • Stretch webbing and foam applied to face |
| Upholstery | <ul style="list-style-type: none"> • All fabric and leather pieces are cut with automated cutters that utilize precise patterns |
| Arms | <ul style="list-style-type: none"> • ¾" (13 gauge) diameter bent powder coated metal tube • 1" thick black resin or beech wood arm cap attached along the top edge via machine screws from underneath |
| Assembly | <ul style="list-style-type: none"> • Seat: Attached to a ¾" x ¾" (16 gauge) powder coated tube frame via ¼" - 20 connector bolts underneath the seat • Back: ¼" thick powder coated metal back brackets attached to the wood frame underneath the foam <ul style="list-style-type: none"> • Brackets and back assembly are attached to the ¾" x ¾" powder coated tube frame via ¼" - 20 connector bolts under seat |

Foam

- | | |
|------|---|
| Seat | <ul style="list-style-type: none"> • 2.5" premium grade foam • CAL TB 117 Certified Fire Retardant • 45 lb. compression • 1.8 density |
| Back | <ul style="list-style-type: none"> • Premium grade foam • CAL TB 117 Certified Fire Retardant |

Suspension

- | | |
|------|--|
| Seat | <ul style="list-style-type: none"> • LEXUS webbing <ul style="list-style-type: none"> • Polypropylene/latex/rubber |
| Back | <ul style="list-style-type: none"> • 2430 Propex <ul style="list-style-type: none"> • 100% Polypropylene • Latex coating is Paranol Acrylic 763 • Applied with 5/16 stainless steel staples |