



Guest chair 1392 / 1392-MT

Overall Dimensions	23.5" w x 25" d x 31.75" h	COM 54"	1.5 yds.
Seat Dimensions	21.25" w x 18.5" d x 18.5" h	Weight	35 lbs.
Seat to Top of Back	13.5"	Cubic Feet	19
Top of Arm to Floor	25.5"	Exposed Metal	Powder Coated Metal Tube



Guest loveseat 1392-L / 1392-L-MT

Overall Dimensions	43.75" w x 25" d x 31.75" h	COM 54"	2.5 yds.
Seat Dimensions	41.5" w x 18.5" d x 18.5" h	Weight	62 lbs.
Seat to Top of Back	13.5"	Cubic Feet	36
Top of Arm to Floor	25.5"	Exposed Metal	Powder Coated Metal Tube



Standard Features	Options Available
<ul style="list-style-type: none"> • 3/4" Tubular bent powder coated metal frame • Black resin arm cap is standard • Upholstered seat and back • Spring seat construction • Clean-thru design • Wall-saver design • Tight cushion • White plastic glide fitted into the bottom of tubular leg • Field replaceable parts 	<ul style="list-style-type: none"> • Poly arm caps (black, taupe, or folkstone grey) • Removable covers

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • 3/4" plywood seat frame panel • Seat springs spanning the openings in the plywood frame • Topped with contour cut foam
Back	<ul style="list-style-type: none"> • 3/4" plywood assembled back frame • Stretch webbing and foam applied to face
Upholstery	<ul style="list-style-type: none"> • All fabric and leather pieces are cut with automated cutters that utilize precise patterns
Arms	<ul style="list-style-type: none"> • 3/4" (13 gauge) diameter bent powder coated metal tube • 1" thick black resin or beech wood arm cap attached along the top edge via machine screws from underneath
Assembly	<ul style="list-style-type: none"> • Seat: Attached to a 3/4" x 3/4" (16 gauge) powder coated tube frame via 1/4" - 20 connector bolts underneath the seat • Back: 1/4" thick powder coated metal back brackets attached to the wood frame underneath the foam <ul style="list-style-type: none"> • Brackets and back assembly are attached to the 3/4" x 3/4" powder coated tube frame via 1/4" - 20 connector bolts under seat

Foam

Seat	<ul style="list-style-type: none"> • 2.5" premium grade foam • CAL TB 117 Certified Fire Retardant • 45 lb. compression • 1.8 density
Back	<ul style="list-style-type: none"> • Premium grade foam • CAL TB 117 Certified Fire Retardant

Suspension

Seat	<ul style="list-style-type: none"> • LEXUS webbing <ul style="list-style-type: none"> • Polypropylene/latex/rubber
Back	<ul style="list-style-type: none"> • 2430 Propex <ul style="list-style-type: none"> • 100% Polypropylene • Latex coating is Paranol Acrylic 763 • Applied with 5/16 stainless steel staples