

**Patient chair 1395**  
Single textiles

<b>Overall Dimensions</b>	23.5"w x 25"d x 45"h	<b>COM 54"</b>	2.25 yds.
<b>Seat Dimensions</b>	21.25"w x 18.5"d x 18.5"h	<b>Weight</b>	41 lbs.
<b>Seat to Top of Back</b>	24"	<b>Cubic Feet</b>	27
<b>Top of Arm to Floor</b>	25.5		
<b>Exposed Metal</b>	Luster Grey		



**Patient chair 1395-MT**  
Multiple textiles

<b>Overall Dimensions</b>	23.5"w x 25"d x 45"h	<b>COM 54" - Seat</b>	1 yd
<b>Seat Dimensions</b>	21.25"w x 18.5"d x 18.5"h	<b>COM 54" - Back</b>	1.75 yds.
<b>Seat to Top of Back</b>	24"	<b>Cubic Feet</b>	24
<b>Top of Arm to Floor</b>	25.5	<b>Weight</b>	55
<b>Exposed Metal</b>	Luster Grey	<b>Weight Rating</b>	300 lbs.



Standard Features	Options Available
<ul style="list-style-type: none"> <li>• 3/4" Tubular Bent Luster Grey Powder Coated Metal Frame</li> <li>• Black Resin Arm Cap</li> <li>• European beech Wood Arm Cap is Optional</li> <li>• Upholstered Seat and Back</li> <li>• Spring Seat Construction</li> <li>• Clean-thru design</li> <li>• Wall-Saver Design</li> <li>• Tight Cushion</li> <li>• White Plastic Glide Fitted into the Bottom of Tubular Leg</li> <li>• Field Replaceable Components</li> </ul>	<ul style="list-style-type: none"> <li>• Wood Arm Caps</li> <li>• Removable Seat and Back Covers</li> <li>• Multiple Fabric Applications</li> <li>• CAL 133 TB Certified</li> <li>• Moisture Barrier</li> </ul>

**Standard Textile & Finish Selection**

---

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

**Frame Construction**

---

- |          |  |
|----------|--|
| Seat     | <ul style="list-style-type: none"><li>• ¾" plywood seat frame panel with seat springs spanning the openings in the plywood frame</li><li>• Topped with contour cut foam</li></ul>  |
| Back     | <ul style="list-style-type: none"><li>• ¾" plywood assembled back frame (chair and loveseat) is covered with a stretch webbing and foam is applied to the face</li></ul>   |
| Arms     | <ul style="list-style-type: none"><li>• Upholstered Arms: 1 ¾" wide x 1 ½" thick molded plywood frame that fits halfway over a metal ¾" (13 gauge) diameter bent tube frame exposing ½ of the powder coated tubular leg</li><li>• Wood Arms: 1 ¾" wide x 1 ½" thick molded European beech frame that fits halfway over a metal ¾" (13 gauge) diameter bent tube frame exposing ½ of the powder coated tubular leg</li><li>• Resin Arms: ¾" black resin arm cap that attaches to the arm via machine screws from underneath</li></ul> |
| Assembly | <ul style="list-style-type: none"><li>• Seat: Attached to a ¾" x ¾" (16 gauge) powder coated tube frame via ¼ - 20 connector bolts</li><li>• Back: ¼" thick powder coated metal back brackets attached to the wood frame underneath the foam</li><li>• The brackets and back assembly are then attached to the ¾" x ¾" powder coated tube frame via ¼ - 20 connector bolts underneath the seat</li></ul>   |

**Foam**

---

- |           |  |
|-----------|--|
| Seat/Back | <ul style="list-style-type: none"><li>• Premium Grade Foam</li><li>• CAL TB 117 Certified Fire Retardant</li></ul> |
|-----------|--|