



Rocker 1476W

Overall Dimensions	30.75" w x 29.5" d x 40.5" h	COM 54"	3.25 yds.
Seat Dimensions	24.5" w x 20" d x 16.75" h	Shipping Weight	60 lbs.
Top of Arm to Floor	24.75"	Cubic Feet	22
		Exposed Metal	Polished Aluminum




High Back Rocker 1480W

Overall Dimensions	30.75" w x 29.5" d x 40.5" h	COM 54"	3.25 yds.
Seat Dimensions	24.5" w x 20" d x 16.75" h	Shipping Weight	63 lbs.
Top of Arm to Floor	24.75"	Cubic Feet	22
		Exposed Metal	Polished Aluminum




Lite Rocker 1476

Overall Dimensions	27.75" w x 29.5" d x 40.5" h	COM 54"	3 yds.
Seat Dimensions	21.5" w x 20" d x 16.75" h	Shipping Weight	57 lbs.
Top of Arm to Floor	24.75"	Cubic Feet	22
		Exposed Metal	Polished Aluminum



Lite/High Back Rocker 1480


Overall Dimensions	27.75" w x 29.5" d x 40.5" h	COM 54"	3.25 yds.
Seat Dimensions	21.25" w x 20" d x 16.75" h	Shipping Weight	60 lbs.
Top of Arm to Floor	24.75"	Cubic Feet	22
		Exposed Metal	Polished Aluminum



Standard Features	Options Available
<ul style="list-style-type: none"> • Clean-Thru Design • Upholstered Seat and Back • Polished Aluminum Cast Legs • Wall-Saver Design • Stationary Arms Standard without Arm Caps • Black Rubber Flooring Track • SCS Indoor Advantage Gold Certified • Limited Lifetime Warranty 	<ul style="list-style-type: none"> • European Beech Wood Arm Caps • Poly Arm Caps (black, taupe or grey) • Solid Surface Arm Caps (cameo white, modern white, concrete, or deep mink) • Adjustable Head Pillow • Motion Arm Lever in Black, Grey or Taupe • Moisture Barrier • CAL TB 133 Certified


Motion Arm, Rocker 1476W-MA

Overall Dimensions	30.75" w x 29.5" d x 40.5" h	COM 54"	3.25 yds.
Seat Dimensions	24.5" w x 20" d x 16.75" h	Shipping Weight	60 lbs.
Top of Arm to Floor	24.75"	Cubic Feet	22
		Exposed Metal	Polished Aluminum




Motion Arm, High Back Rocker 1480W-MA

Overall Dimensions	30.75" w x 29.5" d x 40.5" h	COM 54"	3.25 yds.
Seat Dimensions	24.5" w x 20" d x 16.75" h	Shipping Weight	60 lbs.
Top of Arm to Floor	24.75"	Cubic Feet	22
		Exposed Metal	Polished Aluminum



Motion Arm, Lite Rocker 1476-MA

Overall Dimensions	27.75" w x 29.5" d x 40.5" h	COM 54"	3 yds.
Seat Dimensions	21.5" w x 20" d x 16.75" h	Shipping Weight	57 lbs.
Top of Arm to Floor	24.75"	Cubic Feet	22
		Exposed Metal	Polished Aluminum



Motion Arm, Lite/High Back Rocker 1480-MA

Overall Dimensions	27.75" w x 29.5" d x 46.5" h	COM 54"	3.25 yds.
Seat Dimensions	21.25" w x 20" d x 16.75" h	Shipping Weight	60 lbs.
Top of Arm to Floor	24.75"	Cubic Feet	22
		Exposed Metal	Polished Aluminum



Standard Features	Options Available
<ul style="list-style-type: none"> Clean-Thru Design Upholstered Seat and Back Polished Aluminum Cast Legs Wall-Saver Legs Motion Arms Articulation from Standard Arm Height: 2.5" Up/1.5" Down SCS Indoor Advantage Gold Certified Limited Lifetime Warranty 	<ul style="list-style-type: none"> Poly Arm Caps In Black, Grey or Taupe Solid Surface Arm Caps(4 standards) European Beech Wood Arm Caps Other Powder Coat Options Motion Arm Lever in Black, Grey or taupe Moisture Barrier Multiple Textile Application CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	• Plywood seat frame with molded foam
Back	• Contoured plywood shape with molded foam
Arms	• Cast Aluminum
Assembly	• All bolted connections are 1/4" 20 general grade hardware

Arm Construction

Adjustable	<ul style="list-style-type: none"> Arm Shell: formed rigid foam/mdf Adjustment: ratchet mechanism/resistance gas cylinder Attachment: .25" steel " J" bar Assembly: general grade bolts and stainless steel staples
Fixed	<ul style="list-style-type: none"> Arm Shell: formed rigid foam/mdf Attachment: .25" steel " J" bar Assembly: general grade bolts and stainless steel staples

Foam

Seat/Back	<ul style="list-style-type: none"> Premium grade foam CAL TB 117 Certified Fire Retardant
-----------	---