


Chair 682-1

Overall Dimensions	29"w x 34"d x 44"h	COM 54"	6.25 yds.
Seat Dimensions	22"w x 21"d x 20"h	Weight	80 lbs.
Seat to Top of Back	27"	Cubic Feet	29
Top of Arm to Floor	26"	Exposed Wood	European beech



Loveseat 682-2

Overall Dimensions	50"w x 34"d x 44"h	COM 54"	8.25 yds.
Seat Dimensions	44"w x 21"d x 20"h	Weight	120 lbs.
Seat to Top of Back	27"	Cubic Feet	40
Top of Arm to Floor	26"	Exposed Wood	European beech



Standard Features

- Clean-thru design
- Upholstered arms, seat and back
- Tight cushion
- Tapered European beech legs
- White nail in nylon glide

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- | | |
|------------|---|
| Seat | <ul style="list-style-type: none"> • All components made of kiln dried WHAD maple and plywood • Wood seat EZ frame |
| Upholstery | <ul style="list-style-type: none"> • Required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples |
| Arms | <ul style="list-style-type: none"> • European beech |
| Legs | <ul style="list-style-type: none"> • Dimensions: 7" and 13 7/8" • Machine turned from 6061 aircraft aluminum with clean anodized finish • 5/16" x 18 steel mounting bolt |
| Assembly | <ul style="list-style-type: none"> • Joints on seat, back and arms are assembled using glue, dowels and narrow crown staples |

Foam

- | | |
|------|---|
| Seat | <ul style="list-style-type: none"> • 5" premium grade foam • CAL TB 117 Certified Fire Retardant • 25 compression • 2.5 lb. density • Bonded glue seat |
| Back | <ul style="list-style-type: none"> • Premium grade foam • CAL TB 117 Certified Fire Retardant • 20 compression • 1.8 lb. density • Bonded glue front and rear back |