

**Bariatric chair 1472-OB**  
Single textiles

<b>Overall Dimensions</b>	33.75"w x 26.5"d x 33"h	<b>COM 54"</b>	2.25 yds.
<b>Seat Dimensions</b>	30.25"w x 20"d x 17.75"h	<b>Cubic Feet</b>	28
<b>Seat to Top of Back</b>	15.25"	<b>Weight</b>	58 lbs.
<b>Top of Arm to Floor</b>	25.5"	<b>Weight Rating</b>	500 lbs.
<b>Exposed Metal</b>	Luster Grey		



**Bariatric chair 1472-OB-MT**  
Multiple textiles

<b>Overall Dimensions</b>	33.75"w x 26.5"d x 33"h	<b>COM 54" - Seat</b>	1 yd
<b>Seat Dimensions</b>	30.25"w x 20"d x 17.75"h	<b>COM 54" - Back</b>	1.5 yds.
<b>Seat to Top of Back</b>	15.25"	<b>Cubic Feet</b>	28
<b>Top of Arm to Floor</b>	25.5"	<b>Weight</b>	58 lbs.
<b>Exposed Metal</b>	Luster Grey	<b>Weight Rating</b>	500 lbs.



Standard Features	Options Available
<ul style="list-style-type: none"> <li>Upholstered seat and back</li> <li>Wall-saver design</li> <li>Clean-thru design</li> <li>Tight cushion</li> <li>Luster Grey on all exposed metal</li> <li>Black poly arm caps</li> <li>Rated to 500 lbs.</li> <li>Non-marring adjustable glides</li> <li>Field replaceable components</li> </ul>	<b>Arm caps</b> <ul style="list-style-type: none"> <li>Poly (Black, Taupe, and Grey)</li> <li>Wood (Standard finish offering)</li> <li>Solid surface (Cameo White, Modern White, Medea, and Polaris)</li> </ul>
	<b>Frame</b> <ul style="list-style-type: none"> <li>Powder-coated (standard or super matte powder coats)</li> </ul>
	<b>Shift rear caster</b> <ul style="list-style-type: none"> <li>Caster body will match the specified frame finish</li> </ul> <p><b>Note:</b> Rear casters are for repositioning only, and are not designed for patient transport. Do not move the chair while occupied.</p>

**Standard Textile & Finish Selection**

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

**Frame Construction**

Seat	<ul style="list-style-type: none"> <li>Plywood seat EZ frame construction</li> </ul>
Back	<ul style="list-style-type: none"> <li>Contoured plywood shape 11-ply</li> </ul>
Metal Frame	<ul style="list-style-type: none"> <li>1" 16 gauge C1018 steel posts</li> <li>3/4" x 1/2" 12 gauge C1018 steel rails</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>All fabric and leather pieces are cut with automated cutters that utilize precise patterns</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>All welded joints are full penetration mig/tig welds</li> <li>All bolted connections are 1/4" - 20 grade 5 hardware</li> </ul>

**Foam**

Seat	<ul style="list-style-type: none"> <li>2.25" premium grade foam</li> <li>CAL TB 117 Certified Fire Retardant</li> <li>55 lb. compression</li> <li>2.5 density</li> </ul>
Back	<ul style="list-style-type: none"> <li>1.5" premium grade foam</li> <li>CAL TB 117 Certified Fire Retardant</li> <li>45 lb. compression</li> <li>1.8 density</li> </ul>

**Suspension**

Seat	<ul style="list-style-type: none"> <li>LEXUS webbing <ul style="list-style-type: none"> <li>Polypropylene/latex/rubber</li> </ul> </li> </ul>
Back	<ul style="list-style-type: none"> <li>2430 Propex <ul style="list-style-type: none"> <li>100% Polypropylene</li> <li>Latex coating is Paranol Acrylic 763</li> <li>Applied with 5/16" stainless steel staples</li> </ul> </li> </ul>