

Guest chair 1472

Single textiles

Overall Dimensions	25"w x 26.5"d x 33"h	COM 54"	1.25 yds.
Seat Dimensions	21.5"w x 20"d x 17.75"h	Cubic Feet	18
Seat to Top of Back	15.25"	Weight	45 lbs.
Top of Arm to Floor	25.5"	Weight Rating	400 lbs.
Exposed Metal	Luster Grey		



Guest chair 1472-MT

Multiple textiles

Overall Dimensions	25"w x 26.5"d x 33"h	COM 54" - Seat	1 yd
Seat Dimensions	21.5"w x 20"d x 17.75"h	COM 54" - Back	1 yds.
Seat to Top of Back	15.25"	Cubic Feet	18
Top of Arm to Floor	25.5"	Weight	45 lbs.
Exposed Metal	Luster Grey	Weight Rating	400 lbs.



Guest loveseat 1472-L

Single textiles

Overall Dimensions	45.5"w x 26.5"d x 33"h	COM 54"	2.75 yds.
Seat Dimensions	42.25"w x 20"d x 17.75"h	Cubic Feet	28
Seat to Top of Back	15.25"	Weight	58 lbs.
Top of Arm to Floor	25.5"	Weight Rating	300 lbs. (per seat)
Exposed Metal	Luster Grey		



Guest loveseat 1472-L-MT

Multiple textiles

Overall Dimensions	45.5"w x 26.5"d x 33"h	COM 54" - Seat	1.5 yd
Seat Dimensions	42.25"w x 20"d x 17.75"h	COM 54" - Back	1.5 yds.
Seat to Top of Back	15.25"	Cubic Feet	28
Top of Arm to Floor	25.5"	Weight	58 lbs.
Exposed Metal	Luster Grey	Weight Rating	300 lbs. (per seat)



Standard Features	Options Available
<ul style="list-style-type: none"> Upholstered seat and back Wall-saver design Clean-thru design Tight cushion Luster Grey powder coat on all exposed metal Black poly arm caps Non-marring adjustable glides 	Arm caps <ul style="list-style-type: none"> Poly (Black, Taupe, and Grey) Wood (Standard finish offering) Solid surface (Cameo White, Modern White, Medea, and Polaris)
	Frame <ul style="list-style-type: none"> Powder-coated (standard or super matte powder coats)

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- | | |
|-------------|---|
| Seat | • Plywood seat EZ frame construction |
| Back | • Contoured plywood shape 11-ply |
| Metal Frame | • 16 gauge |
| Assembly | • All welded joints are full penetration mig/tig welds
• All bolted connections are 1/4" 20 grade 5 hardware |

Foam

- | | |
|-----------|--|
| Seat/Back | • 3 lbs, ILD 35 (3-35)
• Premium Grade Foam
• CAL TB 17 Certified Fire Retardant |
|-----------|--|

Suspension

- | | |
|------|--|
| Seat | • LEXUS webbing
• Polypropylene/latex/rubber |
| Back | • 2430 Propex
• 100% Polypropylene
• Latex coating is Paranol Acrylic 763
• Applied with 5/16 stainless steel staples |