


**Guest chair 1472 / 1472-MT**

<b>Overall Dimensions</b>	25"w x 26"d x 33"h	<b>COM 54"</b>	1.5 yds.
<b>Seat Dimensions</b>	21"w x 20"d x 18"h	<b>Weight</b>	45 lbs.
<b>Seat to Top of Back</b>	15.25"	<b>Cubic Feet</b>	19
<b>Top of Arm to Floor</b>	25"	<b>Exposed Metal</b>	Luster grey



**Guest loveseat 1472-L / 1472-L-MT**

<b>Overall Dimensions</b>	45"w x 26"d x 33"h	<b>COM 54"</b>	2.75 yds.
<b>Seat Dimensions</b>	42.25"w x 20"d x 18"h	<b>Weight</b>	70 lbs.
<b>Seat to Top of Back</b>	15.25"	<b>Cubic Feet</b>	33
<b>Top of Arm to Floor</b>	25"	<b>Exposed Metal</b>	Luster grey



Standard Features	Options Available
<ul style="list-style-type: none"> <li>Upholstered seat and back</li> <li>Wall-saver design</li> <li>Clean-thru design</li> <li>Tight cushion</li> <li>Luster Grey powder coat on all exposed metal</li> <li>Black poly arm caps</li> <li>Non-marring adjustable glides</li> </ul>	<ul style="list-style-type: none"> <li>Poly arm caps (black, taupe, and grey)</li> <li>Wood arm caps</li> <li>Solid surface arm caps</li> <li>Removable covers</li> </ul>

**Standard Textile & Finish Selection**

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

**Frame Construction**

Seat	<ul style="list-style-type: none"> <li>Plywood seat EZ frame construction</li> </ul>
Back	<ul style="list-style-type: none"> <li>Contoured plywood shape 11-ply</li> </ul>
Metal Frame	<ul style="list-style-type: none"> <li>16 gauge</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>All welded joints are full penetration mig/tig welds</li> <li>All bolted connections are 1/4" 20 grade 5 hardware</li> </ul>

**Foam**

Seat/Back	<ul style="list-style-type: none"> <li>3 lbs, ILD 35 (3-35)</li> <li>Premium Grade Foam</li> <li>CAL TB 17 Certified Fire Retardant</li> </ul>
-----------	--

**Suspension**

Seat	<ul style="list-style-type: none"> <li>LEXUS webbing <ul style="list-style-type: none"> <li>Polypropylene/latex/rubber</li> </ul> </li> </ul>
Back	<ul style="list-style-type: none"> <li>2430 Propex <ul style="list-style-type: none"> <li>100% Polypropylene</li> <li>Latex coating is Paranol Acrylic 763</li> <li>Applied with 5/16 stainless steel staples</li> </ul> </li> </ul>