

Lounge chair 472-1

Single textiles

Overall Dimensions	27" w x 25.5" d x 31" h	COM 54"	2 yds.	
Seat Dimensions	23" w x 20" d x 18" h	Cubic Feet	12.5	
Seat to Top of Back	13"	Shipping Weight	48.5 lbs.	
Top of Arm to Floor	25"	Weight Rating	400 lbs.	

Lounge chair 472-1-MT

Multiple textiles

Overall Dimensions	27" w x 25.5" d x 31" h	COM 54" - Seat	1.5 yds.	
Seat Dimensions	23" w x 20" d x 18" h	COM 54" - Back	1.75 yds.	
Seat to Top of Back	13"	Cubic Feet	12.5	
Top of Arm to Floor	25"	Shipping Weight	48.5 lbs.	
		Weight Rating	400 lbs.	

Loveseat 472-2

Single textiles

Overall Dimensions	49" w x 25.5" d x 31" h	COM 54"	3.75 yds.	
Seat Dimensions	46" w x 20" d x 18" h	Cubic Feet	23	
Seat to Top of Back	13"	Shipping Weight	81 lbs.	
Top of Arm to Floor	25"	Weight Rating	300 lbs. (per seat)	

Loveseat 472-2-MT

Multiple textiles

Overall Dimensions	49" w x 25.5" d x 31" h	COM 54" - Seat	2 yds.	
Seat Dimensions	46" w x 20" d x 18" h	COM 54" - Back	2.75 yds.	
Seat to Top of Back	13"	Cubic Feet	23	
Top of Arm to Floor	25"	Shipping Weight	81 lbs.	
		Weight Rating	300 lbs. (per seat)	

Sofa 472-3

Single textiles

Overall Dimensions	73" w x 25.5" d x 31" h	COM 54"	5.5 yds.	
Seat Dimensions	69" w x 20" d x 18" h	Cubic Feet	34	
Seat to Top of Back	13"	Shipping Weight	113 lbs.	
Top of Arm to Floor	25"	Weight Rating	300 lbs. (per seat)	

Sofa 472-3-MT

Multiple textiles

Overall Dimensions	73" w x 25.5" d x 31" h	COM 54" - Seat	3.25 yds.	
Seat Dimensions	69" w x 20" d x 18" h	COM 54" - Back	3 yds.	
Seat to Top of Back	13"	Cubic Feet	34	
Top of Arm to Floor	25"	Shipping Weight	113 lbs.	
		Weight Rating	300 lbs. (per seat)	

Standard Features	Options Available
<ul style="list-style-type: none"> Upholstered seat, back, and arms Clean-thru design Tight cushion Wall-saver design Luster Grey powder coat on all exposed metal Black poly arm caps Non-marring adjustable glides 	Arm caps <ul style="list-style-type: none"> Poly (Black, Taupe, and Grey) Wood (Standard finish offering) Solid surface (Cameo White, Modern White, Medea, and Polaris)
	Frame <ul style="list-style-type: none"> Powder-coated (standard or super matte powder coats)

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- | | |
|-------------|--|
| Seat | • 4.5" thick plywood seat box assembly with webbed cutout in top face panel |
| Back | • 7/8" thick plywood assembly, webbed with 1" thick face foam |
| Metal Frame | <ul style="list-style-type: none"> • 1" x 1" 16 gauge C1018 steel posts • 1 1/2" w x .188" thick 7 gauge C1018 mid rails • 1 1/2"w x .750" thick 11 gauge C1018 cross rails |
| Assembly | <ul style="list-style-type: none"> • All welded joints are full penetration mig/tig welds • All bolted connections are 1/4-20 grade 5 hardware • Adjustable Glides: 1/4-20 |

Foam

- | | |
|-----------|--|
| Seat/Back | • All foam is premium grade CAL 117 certified fire retardant |
|-----------|--|

Suspension

- | | |
|------|--|
| Back | <ul style="list-style-type: none"> • Lexus webbing (Polypropylene/latex/rubber) covering the cutout and openings in the seat and back assemblies • 2430 Propex applied to the back face and the back assembly • All applied with 5/16 stainless steel staples |
|------|--|