

# Chair 472-1

Overall Dimensions	27"w x 25.5"d x 31"h	COM 54"	2 yds.	
Seat Dimensions	23"w x 20"d x 18"h	Weight	48.5 lbs.	
Seat to Top of Back	13"	Cubic Feet	12.5	
Top of Arm to Floor	25"			
Loveseat 472-2				
Overall Dimensions	49"w x 25.5"d x 31"h	COM 54"	3.75 yds.	
Seat Dimensions	46"w x 20"d x 18"h	Weight	81 lbs.	
Seat to Top of Back	13"	Cubic Feet	23	
Top of Arm to Floor				
<b>Sofa</b> 472-3				u u
Overall Dimensions	73"w x 25.5"d x 31"h	COM 54"	5.5 yds.	
Seat Dimensions	69"w x 20"d x 18"h	Weight	113 lbs.	
Seat to Top of Back	13"	Cubic Feet	34	
Top of Arm to Floor	25"			

Standard Features	Options Available		
Upholstered seat, back, and arms Tight cushion Wall-saver design Luster Grey powder coat on all exposed metal Black poly arm caps Non-marring adjustable glides	Poly or solid surface arm caps		

# Standard Textile & Finish Selection

Back

Back

http://carolina.ofs.com/resources/textiles http://carolina.ofs.com/resources/finishes

### Frame Construction

• 4.5" thick plywood seat box assembly with webbed cutout in top face panel

• 7/8" thick plywood assembly, webbed with 1" thick face foam

Metal Frame • 1" x 1" 16 gauge C1018 steel posts

•  $1 \frac{1}{2}$ " w x .188" thick 7 gauge C1018 mid rails •  $1\frac{1}{2}$  w x .750" thick 11 gauge C1018 cross rails

• All welded joints are full penetration mig/tig welds Assembly

All bolted connections are 1/4-20 grade 5 hardware

• Adjustable Glides: 1/4-20

# Foam

Seat/Back • All foam is premium grade CAL 117 certified fire retardant

# Suspension

• Lexus webbing (Polypropylene/latex/rubber) covering the cutout and openins in the seat and back assemblies

- 2430 Propex applied to the back face and the back assembly
- All applied with 5/16 stainless steel staples