

Patient Chair 1478

Overall Dimensions	25"w x 26"d x 46.5"h	COM 54"	2.25 yds.
Seat Dimensions	21"w x 20"d x 18"h	Shipping Weight	55 lbs.
Seat to Top of Back	15.25"	Cubic Feet	24
Top of Arm to Floor	25"	Exposed Metal	Luster Grey Powder Coat



Motion Back Patient Chair 1478-M


Overall Dimensions	25"w x 26"d x 46.5"h	COM 54"	2.25 yds.
Seat Dimensions	21.5"w x 20"d x 18"h	Shipping Weight	65 lbs.
Seat to Top of Back	15.25"	Cubic Feet	24
Top of Arm to Floor	25"	Exposed Metal	Luster Grey Powder Coat



Standard Features	Options Available
<ul style="list-style-type: none"> Upholstered Seat and Back Clean-thru Design Wall-Saver Design Tight Cushion Luster Grey Powder Coat on all Exposed Metal Poly Arm Caps (specify color) Non-Marring Adjustable Glides 	<ul style="list-style-type: none"> Poly Arm Caps (black, taupe, or grey) Solid Surface Arm Caps (cameo white, modern white, concrete, or deep mink) CAL 133 TB Certified Moisture Barrier

Easy Access Chair 1474

Overall Dimensions	25"w x 26"d x 40.5"h	COM 54"	1.25 yds.
Seat Dimensions	21.5"w x 17.5"d x 23.75"h	Shipping Weight	60 lbs.
Seat to Top of Back	15.25"	Cubic Feet	24
Top of Arm to Floor	25"	Exposed Metal	Luster Grey Powder Coat



Standard Features	Options Available
<ul style="list-style-type: none"> Upholstered Seat and Back Clean-thru Design Wall-Saver Design Tight Cushion Luster Grey Powder Coat on all Exposed Metal Black Poly Arm Caps Non-Marring Adjustable Glides Polyurethane Coated Steel Foot Rest (specify color) 	<ul style="list-style-type: none"> Poly Arm Caps (black, taupe, or grey) Wood Arm Caps (specify finish) Solid Surface (cameo white, modern white, concrete, deep mink)

Patient Ottoman 1479

Overall Dimensions	18"w x 18.75"d x 13.5"h	COM 54"	0.75 yds.
Seat Dimensions	21.5"w x 17.5"d x 23.75"h	Shipping Weight	12 lbs.
		Cubic Feet	6
		Exposed Metal	Luster Grey Powder Coat



Standard Features
<ul style="list-style-type: none"> Slanted Upholstered Top Luster Grey Powder Coat on all Exposed Metal Tight Cushion Non-Marring Adjustable Glides

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- | | |
|----------|---|
| Seat | • Plywood seat EZ frame construction |
| Back | • Contoured plywood shape 11-ply |
| Arms | • 1" 16 gauge C1018 steel posts
• 3/4" x 1/2" 12 gauge C1018 rails |
| Assembly | • All welded joints are full penetration mig/tig welds
• All bolted connections are 1/4" 20 grade 5 hardware |

Foam

- | | |
|-----------|--|
| Seat/Back | • All foam is premium grade CAL 117 certified fire retardant |
|-----------|--|

Suspension

- LEXUS webbing
- Polypropylene/latex/rubber
- 2430 propex (applied to backs)
- 100% polypropylene
- Latex coating is paranol acrylic 763
- Applied with 5/16 stainless steel staples