



**Guest chair 1471 / 1471-MT**

<b>Overall Dimensions</b>	25" w x 26" d x 33" h	<b>COM 54"</b>	1.5 yds.
<b>Seat Dimensions</b>	21" w x 18.5" d x 19" h	<b>Weight</b>	60 lbs.
<b>Seat to Top of Back</b>	14.25"	<b>Cubic Feet</b>	21
<b>Top of Arm to Floor</b>	25"	<b>Exposed Wood</b>	European Beech
<b>Exposed Metal</b>	Warm Grey Powder Coat		



**Guest loveseat 1471-L / 1471-L-MT**

<b>Overall Dimensions</b>	45.25" w x 26" d x 33" h	<b>COM 54"</b>	2.75 yds.
<b>Seat Dimensions</b>	41.75" w x 18.5" d x 19" h	<b>Weight</b>	85 lbs.
<b>Seat to Top of Back</b>	14.25"	<b>Cubic Feet</b>	36
<b>Top of Arm to Floor</b>	25"	<b>Exposed Wood</b>	European Beech
<b>Exposed Metal</b>	Warm Grey Powder Coat		



Standard Features	Options Available
<ul style="list-style-type: none"> <li>Clean-thru design</li> <li>Upholstered seat and back</li> <li>Field replaceable components</li> <li>European beech arm caps</li> <li>Warm Grey (with silver ion antimicrobial) powder coat on all exposed metal is standard</li> <li>Wall-saver design</li> <li>Non-marring adjustable glides</li> </ul>	<ul style="list-style-type: none"> <li>Wood arm caps</li> <li>Poly arm caps (black, taupe, or grey)</li> <li>Removable covers</li> </ul>

**Standard Textile & Finish Selection**

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

**Frame Construction**

<b>Seat</b>	<ul style="list-style-type: none"> <li>Plywood seat EZ frame</li> </ul>
<b>Back</b>	<ul style="list-style-type: none"> <li>Contoured plywood shape 11-ply</li> </ul>
<b>Upholstery</b>	<ul style="list-style-type: none"> <li>All fabric and leather pieces are cut with automated cutters that utilize precise patterns</li> </ul>
<b>Metal Frame</b>	<ul style="list-style-type: none"> <li>1" 16 gauge C1018 steel posts</li> <li>3/4" x 1/2" 12 gauge C1018 steel rails</li> </ul>
<b>Assembly</b>	<ul style="list-style-type: none"> <li>All welded joints are full penetration mig/tig welds</li> <li>All bolted connections are 1/4" 20 grade 5 hardware</li> </ul>

**Foam**

<b>Seat</b>	<ul style="list-style-type: none"> <li>2.25" premium grade foam</li> <li>CAL TB 117 Certified Fire Retardant</li> <li>55 lb. compression</li> <li>2.5 density</li> </ul>
<b>Back</b>	<ul style="list-style-type: none"> <li>1.5" premium grade foam</li> <li>CAL TB 117 Certified Fire Retardant</li> <li>45 lb. compression</li> <li>1.8 density</li> </ul>

**Suspension**

<b>Seat</b>	<ul style="list-style-type: none"> <li>LEXUS webbing                             <ul style="list-style-type: none"> <li>Polypropylene/latex/rubber</li> </ul> </li> </ul>
<b>Back</b>	<ul style="list-style-type: none"> <li>2430 Propex                             <ul style="list-style-type: none"> <li>100% Polypropylene</li> <li>Latex coating is Paranol Acrylic 763</li> <li>Applied with 5/16" stainless steel staples</li> </ul> </li> </ul>