


Guest chair 1441 / 1441-MT

Overall Dimensions	25" w x 26" d x 33" h	COM 54"	1.5 yds.
Seat Dimensions	21" w x 18.5" d x 19" h	Weight	60 lbs.
Seat to Top of Back	14.25"	Cubic Feet	20
Top of Arm to Floor	25"	Exposed Wood	European Beech
Exposed Metal	Warm Grey Powder Coat		



Guest loveseat 1441-L / 1441-L-MT

Overall Dimensions	48" w x 26" d x 33" h	COM 54"	2.75 yds.
Seat Dimensions	41.25" w x 18.5" d x 19" h	Weight	85 lbs.
Seat to Top of Back	14.25"	Cubic Feet	46
Top of Arm to Floor	25"	Exposed Wood	European Beech
Exposed Metal	Warm Grey Powder Coat		



Standard Features	Options Available
<ul style="list-style-type: none"> Clean-thru design Upholstered seat and back Field replaceable components European beech arm caps and overlay on legs Warm Grey (with silver ion antimicrobial) powder coat on all exposed metal is standard Wall-saver design Non-marring adjustable glides 	<ul style="list-style-type: none"> Wood arm caps Poly arm caps (black, taupe or grey) Removable covers

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> Plywood seat EZ frame
Back	<ul style="list-style-type: none"> Contoured plywood shape 11-ply
Upholstery	<ul style="list-style-type: none"> All fabric and leather pieces are cut with automated cutters that utilize precise patterns
Frame	<ul style="list-style-type: none"> 1" 16 gauge C1018 steel posts 3/4" x 1/2" 12 gauge C1018 steel rails Covered with European Beech hardwoods
Assembly	<ul style="list-style-type: none"> All welded joints are full penetration mig/tig welds All bolted connections are 1/4" 20 grade 5 hardware

Foam

Seat	<ul style="list-style-type: none"> 2.25" premium grade foam CAL TB 117 Certified Fire Retardant 55 lb. compression 2.5 density
Back	<ul style="list-style-type: none"> 1.5" premium grade foam CAL TB 117 Certified Fire Retardant 45 lb. compression 1.8 density

Suspension

Seat	<ul style="list-style-type: none"> LEXUS webbing <ul style="list-style-type: none"> Polypropylene/latex/rubber
Back	<ul style="list-style-type: none"> 2430 Propex <ul style="list-style-type: none"> 100% Polypropylene Latex coating is Paranol Acrylic 763 Applied with 5/16" stainless steel staples