

Physician's stool 2500

Overall Dimensions	26"w x 26"d x 15.5-20.75"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 15.5-20.75"h	Shipping Weight	20 lbs.	
		Cubic Feet	9	

Physician's stool 2501

Overall Dimensions	26"w x 26"d x 19.25-26.5"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 19.25-26.5"h	Shipping Weight	20 lbs.	
		Cubic Feet	11	

Lab stool 2502

Overall Dimensions	26"w x 26"d x 23-33"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 23-33"h	Shipping Weight	20 lbs.	
Footring diameter	20"	Cubic Feet	11	



Lab stool with back 2500-B

Overall Dimensions	26"w x 26"d x 25.5-30.75"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 25.5-30.75"h	Shipping Weight	23 lbs.	
Inside Back	20"	Cubic Feet	14	
Footring diameter	20"			

Lab stool with back 2501-B

Overall Dimensions	26"w x 26"d x 29.25-36.5"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 29.25-36.5"h	Shipping Weight	23 lbs.	
Inside Back	20"	Cubic Feet	14	
Footring diameter	20"			

Lab stool with back 2502-B

Overall Dimensions	26"w x 26"d x 33-43"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 33-43h	Shipping Weight	23 lbs.	
Inside Back	20"	Cubic Feet	14	
Footring diameter	20"			

Standard Features	Options
- Height adjustable, pneumatic lift located under seat 5 star base available in Carbon, Graphite, and Chalk - Seat pan available in Carbon, Graphite and Chalk - Black hard wheel casters are standard	- Foot ring - Black soft wheel casters - Black glides

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	- Standard with 3/4", one-piece multicore hardwood plywood seat. - All plywood seats are fitted with Riveted "T" Nuts fixed on both sides of the plywood - Injection molded seat cover made out of polypropylene
Back	Optional plastic back is constructed of injection-molded, glass-reinforced nylon resin
Upholstery	Seat upholstery is available in hundreds of fabrics. All fabrics meet CAL Tech Bulletin 117-2013
Control	- Rated up to 300 lbs. - Height adjustable with 360° ring actuator
Base	- Low-profile chair base is manufactured of solid injection-molded, glass-reinforced nylon resin - Low-profile Polished Aluminum chair base is constructed from die cast aluminum and meets ANSI/BIFMA strenght and durability requirements
Cylinder	Our variety of Class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon. The large pivot barrels provide a smooth visual transition to the chair base.
Assembly	Self-locking, hardened steel, Hex/Socket/Phillips head bolts hold the seat control to the seat cover. All bolts are treated with "NYLOK" to prevent bolts from loosening due to vibration

Foam

Seat	- The seat cushion features 1.75" thick, high resilience molded foam - The IFD (Internal Force Detection) has been carefully selected for overall durability and comfort - CAL 117-2013 50 IFD 3.0 lb. Density
------	--