







Physician's stool 2500

Overall Dimensions	26"w x 26"d x 15.5-20.75"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 15.5-20.75"h	Weight	20 lbs.	
		Cubic Feet	9	



Physician's stool 2501

Overall Dimensions	26"w x 26"d x 19.25-26.5"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 19.25-26.5"h	Weight	20 lbs.	
		Cubic Feet	11	



Lab stool 2502

Overall Dimensions	26"w x 26"d x 23-33"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 23-33"h	Weight	20 lbs.	
Footring diameter	20"	Cubic Feet	11	



Physician's stool with back 2500-B

Overall Dimensions	26"w x 26"d x 25.5-30.75"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 15.5-20.75"h	Weight	23 lbs.	
Inside Back	10"	Cubic Feet	14	
Footring diameter	20"			

Physician's stool with back 2501-B

Overall Dimensions	26"w x 26"d x 29.25-36.5"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 19.25-26.5"h	Weight	23 lbs.	
Inside Back	10"	Cubic Feet	14	
Footring diameter	20"			

Lab stool with back 2502-B

Overall Dimensions	26"w x 26"d x 33-43"h	COM 54"	0.75 yds.	 
Seat Diameter	16.25"w x 16.25"d x 23-33"h	Weight	23 lbs.	
Inside Back	10"	Cubic Feet	14	
Footring diameter	20"			

Standard Features	Options
<ul style="list-style-type: none"> <li>Height adjustable, pneumatic lift located under seat</li> <li>5 star base available in Carbon, Graphite, and Chalk</li> <li>Seat pan available in Carbon, Graphite and Chalk</li> <li>Black hard wheel casters are standard</li> </ul>	<ul style="list-style-type: none"> <li>Foot ring</li> <li>Black soft wheel casters</li> <li>Black glides</li> </ul>

## Standard Textile & Finish Selection

---

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

## Frame Construction

---

Seat	<ul style="list-style-type: none"> <li>Standard with 3/4", one-piece multicore hardwood plywood seat.</li> <li>All plywood seats are fitted with Riveted "T" Nuts fixed on both sides of the plywood</li> <li>Injection molded seat cover made out of polypropylene</li> </ul>
Back	<ul style="list-style-type: none"> <li>Optional plastic back is constructed of injection-molded, glass-reinforced nylon resin</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>Seat upholstery is available in hundreds of fabrics. All fabrics meet CAL Tech Bulletin 117-2013</li> </ul>
Control	<ul style="list-style-type: none"> <li>Rated up to 300 lbs.</li> <li>Height adjustable with 360° ring actuator</li> </ul>
Base	<ul style="list-style-type: none"> <li>Low-profile chair base is manufactured of solid injection-molded, glass-reinforced nylon resin</li> <li>Low-profile Polished Aluminum chair base is constructed from die cast aluminum and meets ANSI/BIFMA strenght and durability requirements</li> </ul>
Cylinder	<ul style="list-style-type: none"> <li>Our variety of Class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li> </ul>
Casters	<ul style="list-style-type: none"> <li>Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon. The large pivot barrels provide a smooth visual transition to the chair base.</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>Self-locking, hardened steel, Hex/Socket/Phillips head bolts hold the seat control to the seat cover. All bolts are treated with "NYLOK" to prevent bolts from loosening due to vibration</li> </ul>

## Foam

---

Seat	<ul style="list-style-type: none"> <li>The seat cushion features 1.75" thick, high resilience molded foam</li> <li>The IFD (Internal Force Detection) has been carefully selected for overall durability and comfort</li> <li>CAL 117-2013</li> <li>50 IFD</li> <li>3.0 lb. Density</li> </ul>
------	--