


Bariatric Chair 1520-OB

Overall Dimensions	33"w x 26.5"d x 34"h	COM 54"	2 yds.
Seat Dimensions	30"w x 19.5"d x 17"h	Shipping Weight	55 lbs.
Seat to Top of Back	17"	Cubic Feet	28
Top of Arm to Floor	25.5"	Exposed Wood	European Beech



Bariatric Chair 1520-K

Overall Dimensions	34"w x 26.5"d x 34"h	COM 54"	2 yds.
Seat Dimensions	30"w x 19.5"d x 17"h	Shipping Weight	60 lbs.
Seat to Top of Back	17"	Cubic Feet	28
Top of Arm to Floor	25.5"	Exposed Wood	European Beech



Standard Features	Options Available
<ul style="list-style-type: none"> • 500 lbs. weight rating (1520-OB) • 1000 lbs. weight rating (1520-K) • European Beech exterior frame • Clean-Thru design • Upholstered seat and back • Wall-Saver design • Non-marring adjustable glides • SCS Indoor Advantage Gold Certified • Limited lifetime warranty • QuickShip 	<ul style="list-style-type: none"> • Poly arm caps (black) • Removable covers • Moisture barrier • Multiple textile application • CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- | | |
|------------|---|
| Seat | <ul style="list-style-type: none">• WHAD kiln dried maple• Plywood seat EZ frame |
| Back | <ul style="list-style-type: none">• Back is made of WHAD kiln dried maple |
| Arms | <ul style="list-style-type: none">• All components are made of kiln dried European Beech |
| Upholstery | <ul style="list-style-type: none">• All fabric and leather pieces are cut with automated cutters that utilize precise patterns |
| Assembly | <ul style="list-style-type: none">• Joints on seat, back, and arms are assembled using dowels, Mortise-and-Tenons, blocks, glue and #8/#10 screws |

Foam

- | | |
|------|--|
| Seat | <ul style="list-style-type: none">• 2" premium grade foam• CAL TB 117 Certified Fire Retardant• 55 lb. compression• 2.5 density• Covered in .75 oz of polyester fiber then cemented to the frame |
| Back | <ul style="list-style-type: none">• 1.25" premium grade foam• CAL TB 117 Certified Fire Retardant• 55 lb. compression• 2.5 density• All foam is contour cut to follow the design |

Suspension

- | | |
|------|--|
| Seat | <ul style="list-style-type: none">• LEXUS webbing<ul style="list-style-type: none">• Polypropylene/latex/rubber |
| Back | <ul style="list-style-type: none">• 2430 Propex<ul style="list-style-type: none">• 100% Polypropylene• Latex coating is Paranol Acrylic 763• Applied with $\frac{5}{16}$" stainless steel staples |