


Patient Chair 1525

Motion Patient Chair 1525-Motion

| | | | |
|----------------------------|------------------------|------------------------|----------------|
| Overall Dimensions | 24"w x 26.5"d x 43.5"h | COM 54" | 2.25 yds. |
| Seat Dimensions | 21"w x 19"d x 18"h | Shipping Weight | 45 lbs. |
| Seat to Top of Back | 23" | Cubic Feet | 25 |
| Top of Arm to Floor | 25.5" | Exposed Wood | European Beech |



| Standard Features | Options Available |
|---|---|
| <ul style="list-style-type: none"> • 1525-Motion mechanism design specific with up to 8° of smooth travel • European Beech Open Arm Frame • European Beech Exterior Frame • Clean-Thru Design • Upholstered Seat and Back • Non-Marring Adjustable Glides • Euroluxe® Finishes with SilverBan® • SCS Indoor Advantage Gold Certified • Limited Lifetime Warranty | <ul style="list-style-type: none"> • Poly Arm Caps in Black • Back Bump Guard • Removable Covers • Moisture Barrier • Multiple Textile Application • CAL TB 133 Certified |

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

| | |
|------------|---|
| Seat | <ul style="list-style-type: none"> • Plywood seat EZ frame • Seat wedge; kiln dried WHAD maple (1525-Motion only) |
| Back | <ul style="list-style-type: none"> • All components are made of WHAD kiln dried maple |
| Upholstery | <ul style="list-style-type: none"> • All fabric and leather pieces are cut with automated cutters that utilize precise patterns |
| Arms | <ul style="list-style-type: none"> • All components are made of kiln dried European Beech |
| Assembly | <ul style="list-style-type: none"> • Joints on seat, back and arms are assembled using dowels, mortise-and-tenons, corner blocks, glue and #8/#10 screws |

Foam

| | |
|-----------|---|
| Seat/Back | <ul style="list-style-type: none"> • Premium Grade Foam • CAL TB 117 Certified Fire Retardant |
|-----------|---|

Suspension

| | |
|------|--|
| Seat | <ul style="list-style-type: none"> • LEXUS webbing <ul style="list-style-type: none"> • Polypropylene/latex/rubber • The webbing contains about 40% latex, but is encapsulated by polypropylene yarn (1525 only) |
| Back | <ul style="list-style-type: none"> • 2430 Propex <ul style="list-style-type: none"> • 100% Polypropylene • Latex Coating is Paranol Acrylic 763 • Applied with 5/16" Stainless Steel Staples |

Seat Pan and Travel Mechanism

- 7 gauge thick welded steel
- Seat and Back Support Brackets is of 7 gauge thick "C" Channel Steel (1525-Motion only)
- Mechanism is design specific with up to 8° of smooth travel, and has been tested to more than 145,000 cycles with no loss of torque (1525-Motion only)