


Edges		Pulls	
			
Square edge	Knife edge	Batten	Integrated

Standard finish selection

<https://ofs.com/resources/finishes>

- | | |
|---------------|--|
| Veneer | <ul style="list-style-type: none"> • Standard and studio veneers • Quartered or flat cut |
| Solid surface | <ul style="list-style-type: none"> • Standard solid surface offering |

Series details

- | | |
|-----------------------------|--|
| Heights | <ul style="list-style-type: none"> • Fixed worksurface height: 29.5"h • Low height storage: 22.25"h • Series overall height: 68.25"h |
| Storage levelers | <ul style="list-style-type: none"> • Storage components features extruded aluminum foot design with integrated leg levelers • Adjustable levelers allow for up to .75" of leveling |
| Metal leg and foot finishes | <ul style="list-style-type: none"> • Black, Bronze, Polished Aluminum, or Satin Nickel |
| Pulls | <ul style="list-style-type: none"> • Two pull options: extruded aluminum batten pull or Integrated finger pull • Extruded aluminum batten in Black, Bronze, Polished Aluminum, or Satin Nickel • Integrated finger pull to match finish of unit |
| Glass | <ul style="list-style-type: none"> • Available on overlay worksurfaces and sliding glass organizer doors • Clear, White back paint, Bronze tint or Black tint |
| Grommets | <ul style="list-style-type: none"> • Available on built up static desks and modular worksurfaces • Round grommet • Factory installed • Black or Polished Aluminum |
| Task lighting | <ul style="list-style-type: none"> • Optional high efficiency LED task lighting for wallmount and highback organizers • Recesses into the bottom of overhead • Multiple task lights can be daisy chained together to operate off one remote |

Worksurfaces

- | | |
|----------------------------|--|
| Construction/
materials | <ul style="list-style-type: none"> • 1.1875" thick for desk height worksurfaces • .75" thick for low height worksurfaces • Veneer <ul style="list-style-type: none"> - 3-ply construction • Solid surface • Glass: .5" thick tempered glass |
| Overlay surfaces | <ul style="list-style-type: none"> • Veneer and glass: includes veneer subtop (3-ply construction) • Solid surface: includes black gator subtop with veneer edge |
| Edge | <ul style="list-style-type: none"> • Square edge: 2mm wood edge • 2" flat knife edge: 1mm wood edge <ul style="list-style-type: none"> - Optional on height adjustable - Standard on solid surface and conference tops • Primary worksurfaces are profiled on approach and user sides • Secondary worksurfaces are profiled on user side only |



Height adjustable components

- | | |
|-----------------|--|
| Lift mechanism | <ul style="list-style-type: none">• 3 stage column constructed out of 2mm thick powder coated steel• 27"-46.5" height range, 19.5" stroke• Uses 1/4" thick steel mounting plates• 10' power cord, 8'6" of usable cord length• Table maximum weight allowance is 75 lbs |
| Controller | <ul style="list-style-type: none">• Standard button height adjustable controller<ul style="list-style-type: none">- Three preset heights• Optional paddle switch height adjustable controller<ul style="list-style-type: none">- One preset height |
| Wire management | <ul style="list-style-type: none">• Field installed worksurface and base cabinet grommet is recommend for wire management |
| Power | <ul style="list-style-type: none">• Optional PS-77 power supply |
| Shipping | <ul style="list-style-type: none">• Ships KD. Top, cabinet, and base components ship separately |

Drawers

- | | |
|--------------------|---|
| Construction | <ul style="list-style-type: none">• Unidirectional plywood grained engineered composite wood material butt-jointed and doweled construction• Drawer sides and backs are .46875" thick• Drawer bottoms are .25" thick• Drawer fronts are field replaceable• Full extension progressive action slides with steel ball bearing suspensions |
| Filing and storage | <ul style="list-style-type: none">• File rails included in all file drawers to accommodate letter or legal filing |

Metal bases

- | | |
|-----------------|---|
| Construction | <ul style="list-style-type: none">• Extruded aluminum• Adjustable levelers allow for up to .5" of leveling |
| Wire management | <ul style="list-style-type: none">• Includes cable management cavity in column with top and bottom retaining clips |

Locking

- Storage standard as non-locking
- Locking available on drawers and doors at an upcharge
- **Note:** Locking not available on glass doors
- All locking is located on the front of pedestal or door
- All units ship keyed alike unless specified differently. **Note:** Specific key requirements may be specified on the purchase order at the time the order is placed for field installation (ship separately)
- Removable lock cores for re-keying

Benching electrical

- 4 circuit / 8 wire electrical system
- UL listed