



Standard finish selection

<https://ofs.com/resources/finishes>

Frame construction

-
- | | |
|------------|--|
| Base plate | <ul style="list-style-type: none">• Steel components with mechanical fastener construction• Standard and studio powder coats |
| Column | <ul style="list-style-type: none">• Welded tube steel components are powder coated• 211-1919S has fixed column• 211-1919P has pneumatic column |
| Foot | <ul style="list-style-type: none">• Cast aluminum with mechanical fastener construction |
| Top | <ul style="list-style-type: none">• 1" Thick TFL with 2mm PP edge banding with flat edge• 1" Thick HPL with 2mm PP edge banding with flat edge• 1" Thick painted with flat edge• 1" Thick veneer with 2mm wood edge banding (3 edge shape options)• 1" Thick HPL with plywood knife edge• 1" Thick solid surface with bullnose edge |

Finish selection

-
- | | |
|---------------|--|
| Veneer | <ul style="list-style-type: none">• Flat or quartered |
| HPL/TFL | <ul style="list-style-type: none">• Available in wood grain and solid colors |
| Solid surface | <ul style="list-style-type: none">• Standard solid surface |

Power

-
- 6' of usable cord on all power supplies beyond the column

Wire management

-
- Wire management is integrated into columns for in surface and under surface power

Glides

-
- Fixed glides on pull up table
 - UHMW polyethylene glide material
 - Adjustable glides extend .25" on occasional, dining and conference tables

Carton/packaging

-
- All bases and tops will come separately in their own cartons