


Low back all purpose chair 93015

Overall dimensions	28.5"w x 28.5"d x 33.5-38.5"h	Weight	22.5 lbs.
Seat dimensions	18"w x 18.25"d x 17.5-22.5"h	Cubic feet	18
Seat to top of back	13"	COM	.75 yds.
Top of arm to floor	25.5/30.5"	COL	15 sq. ft.
Top of arm to seat	7.5"		



Standard features	Options available
<ul style="list-style-type: none"> <li>Fixed arms</li> <li>Upholstered seat</li> <li>Molded plastic shell</li> <li>Polished aluminum 4-star base</li> <li>Polished gas cylinder</li> </ul>	<ul style="list-style-type: none"> <li>Finish available in Carbon or Cloud <ul style="list-style-type: none"> <li>Carbon frame with Carbon arm pads</li> <li>Cloud frame with grey arm pads</li> </ul> </li> <li>Soft wheel casters</li> <li>Glides</li> <li>Fully assembled</li> </ul>

Construction

Shell	<ul style="list-style-type: none"> <li>The one-piece plastic shell is constructed of injection-molded, glass-reinforced nylon resin</li> <li>Carbon or Cloud finish option</li> </ul>
Upholstery	<ul style="list-style-type: none"> <li>All fabrics meet CAL Tech Bulletin 117-2013</li> </ul>
Arms	<ul style="list-style-type: none"> <li>Integrated, fixed cantilever arms with polypropylene arm pad</li> <li>Carbon frame with Carbon arm pads</li> <li>Cloud frame with grey arm pads</li> </ul>
Controls	<ul style="list-style-type: none"> <li>Swivel tilt mechanism with height adjustment</li> </ul>
Bases	<ul style="list-style-type: none"> <li>4 Star polished base is constructed from die cast aluminum and meets ANSI/BIFMA strength and durability requirements</li> </ul>
Cylinder	<ul style="list-style-type: none"> <li>Our variety of Class 4 gas cylinders, meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria</li> </ul>
Casters	<ul style="list-style-type: none"> <li>Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon and contain 60mm diameter large pivot barrels.</li> </ul>