


Edges	Pulls
 EY - Square	 Aero  Integrated finger pull

Finish selection

Standard laminates <http://ofs.com/resources/finishes>

Standard and studio powdercoats <http://ofs.com/resources/finishes>

Edges and Pulls

- | | |
|-------|--|
| Edges | <ul style="list-style-type: none"> Square edge |
| Pulls | <ul style="list-style-type: none"> Aero pull available in standard and studio powder coats AS-Integrated finger pull - all fronts below worksurface will require Upper Door Storage to use touch latch |

Grommets

- Grommet finish: Black or Satin Nickel

Worksurfaces

- Desk tops are 1" thick
- Laminate worksurfaces are thermally fused with a 2mm polypropylene edge
- Tops available in HPL
- Primary and secondary worksurfaces are profiled on approach and user sides
- Durable scratch resistant matte finish on all units

Height adjustable worksurfaces

- | | |
|----------------|--|
| Casegoods | <ul style="list-style-type: none"> Height adjustability on double pedestal desk, single pedestal desk, and bridges 29.75-45.75 height range Uses 1/4" thick steel mounting plates |
| Lift mechanism | <ul style="list-style-type: none"> 2 stage column constructed out of 2mm thick powder coated steel Intuitive desk panel for simple up and down drive (Black) |

Pedestals

- Pedestals are full height
- File drawers have full extension, progressive action slides with steel ball bearing suspensions
- File drawer sides and backs are .5" thick, drawer bottoms are .25" thick
- File rails include in all file drawers to accommodate letter or legal filing
- Drawers are mitre fold dark maple vinyl wrapped particleboard
- Woodgrain patterned drawer sides provide a consistent appearance and are stain resistant and easily cleaned
- All drawer slides and door hinges are soft close
- Pedestal and storage glides allow for up to 1.25" of leveling
- Drawer fronts are field replaceable

Wire management

- Wire management is standard in returns, bridge units, credenzas, corner units and hutch units

Upper storage

- Upper storage components are .75" thick TFL with 2mm edgebanding
- All door hinges and slides are soft close



Locking

- Standard non-locking
- Locking options are available at an upcharge
- All locking is located on the front of pedestal
- Drawer front locks secure all drawers with the turn of a single key
- All units ship keyed alike unless specified differently
- Removable lock cores for re-keying

Specific key requirements may be specified on the purchase order at the time the order is placed for field installation (ship separately)