

Edges 1" Thick		Pulls			
					
Square (DN) (veneer)	Square (EY) (HPL)	Grip	Era	Axis	Awe
Edges 1.5625" Thick					
					
Square (AE) (veneer only)		Empire	Icon	Forte	Crest

Standard finish selection

<http://ofs.com/resources/finishes>

- | | |
|-------------|---|
| Veneer | <ul style="list-style-type: none"> Standard and studio veneers Quartered or flat cut |
| Laminate | <ul style="list-style-type: none"> Standard and studio woodgrain HPL laminates Note: HPL laminates applied to worksurfaces only. Chassis will default to matching veneer |
| Powder coat | <ul style="list-style-type: none"> Standard and studio powder coats |

Series details

- | | |
|--------------------|--|
| Heights | <ul style="list-style-type: none"> Fixed worksurface height: <ul style="list-style-type: none"> - 1" thick worksurface: 30"h - 1.5625" thick worksurface: 30.375"h Bench height storage: 19"h Series overall height: 72"h or 84"h |
| Pulls | <ul style="list-style-type: none"> Eight options: Grip, Era, Axis, Awe, Empire, Icon, Crest, or Forte Standard or studio powder coats |
| Grommets | <ul style="list-style-type: none"> Rectangular grommet Factory installed Optional on all worksurfaces Grommet finish is based off of the hardware/pull color chosen Black grommet when these powder coat colors are selected: Onyx, Gold, Graphite, Oiled Bronze, or Soft Bronze Satin Nickel grommet when these powder coat colors are selected: Bone White, Chalk, Luster Grey, Polar, Warm Grey, or Stone |
| Power and charging | <ul style="list-style-type: none"> Optional USB charging located in upper box drawer of built up and height adjustable pedestal desks |

Worksurfaces

- | | |
|----------------------------|---|
| Construction/
materials | <ul style="list-style-type: none"> 1" or 1.5625" thick worksurfaces 3-ply construction Optional HPL worksurfaces - high pressure laminate |
| Edge | <ul style="list-style-type: none"> Square edge: 2mm wood edge Primary worksurfaces are profiled on approach and user sides Secondary worksurfaces are profiled on user side only |



Height adjustable worksurfaces

- | | |
|-------------------------|--|
| Lift mechanism | <ul style="list-style-type: none">• 2 stage column constructed out of 2mm thick powder coated steel• 30 ½"-46" height range, 16" stroke• 10.5 ft. cord length<ul style="list-style-type: none">- Built up height adjustable units have 4 ft. slack at max height adjustment• Table maximum weight allowance is 75 lbs |
| Controller | <ul style="list-style-type: none">• Standard button height adjustable controller• Three preset heights |
| Built up units | <ul style="list-style-type: none">• Leg mechanism is visible when worksurface is raised• Uses ¼" thick steel mounting plates |
| Arc base | <ul style="list-style-type: none">• Leg mechanism is fully concealed when worksurface is raised• Note: Arc base runoff leg mechanism is visible at bench end• Uses L bracket that is attached to the top and leg mechanism |
| Freestanding metal base | <ul style="list-style-type: none">• Square leg profile• Feet are ½" thick powder coated steel with adjustable glides• Table bridges include a ¼" thick steel mounting plate to attach to the worksurface |

Drawers

- | | |
|--------------------|---|
| Construction | <ul style="list-style-type: none">• Unidirectional plywood grained engineered composite wood material butt-jointed and doweled construction• Drawer sides and back are .4375" thick• Drawer bottoms are .25" thick• Full extension progressive action slides with steel ball bearing suspensions• Drawer fronts are field replaceable |
| Filing and storage | <ul style="list-style-type: none">• File rails included in all file drawers to accommodate letter or legal filing |

Locking

- Pedestal storage standard with locking
- Optional locking on doors
- **Note:** Locking not available on hinged doors with glass or acrylic inserts
- Locking is located on the interior side of drawer pedestals, and the front of pedestal or door
- All units ship keyed alike unless specified differently. **Note:** Specific key requirements may be specified on the purchase order at the time the order is placed for field installation (ship separately)
- Removable lock cores for re-keying